



VOLVO

OIL ANALYSIS REPORT



Area
[SPM659044-10]
 Machine Id
VOLVO A40G 341625
 Component
Transmission (Auto)
 Fluid
VOLVO AT 102 (--- GAL)

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		VCP438921	VCP393790	VCP344748
Sample Date		Client Info		11 Jan 2024	17 Mar 2023	12 Oct 2021
Machine Age	hrs	Client Info		8515	7472	5457
Oil Age	hrs	Client Info		0	2015	0
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	Changed	N/A
Filter Changed		Client Info		Changed	Changed	N/A
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>160	18	20	18
Chromium	ppm	ASTM D5185m	>5	0	0	<1
Nickel	ppm	ASTM D5185m	>5	2	5	5
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m	>5	0	0	<1
Aluminum	ppm	ASTM D5185m	>50	4	11	8
Lead	ppm	ASTM D5185m	>50	0	0	0
Copper	ppm	ASTM D5185m	>225	16	32	27
Tin	ppm	ASTM D5185m	>10	<1	4	<1
Vanadium	ppm	ASTM D5185m		0	0	<1
White Metal	scalar	*Visual	NONE	NONE	NONE	VLITE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION










There is no indication of any contamination in the fluid.

Silicon	ppm	ASTM D5185m	>20	3	3	5
Potassium	ppm	ASTM D5185m	>20	<1	<1	8
Water		WC Method	>0.1	NEG	NEG	NEG
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	VLITE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG

FLUID CONDITION

The condition of the fluid is acceptable for the time in service.

Sodium	ppm	ASTM D5185m		3	3	4
Boron	ppm	ASTM D5185m	187	90	90	82
Barium	ppm	ASTM D5185m	0.0	0	0	0
Molybdenum	ppm	ASTM D5185m	0.0	<1	<1	<1
Manganese	ppm	ASTM D5185m	0.0	<1	<1	<1
Magnesium	ppm	ASTM D5185m	6.8	1	2	4
Calcium	ppm	ASTM D5185m	215	79	77	105
Phosphorus	ppm	ASTM D5185m	445	201	190	179
Zinc	ppm	ASTM D5185m	56	3	6	8
Sulfur	ppm	ASTM D5185m	1336	2016	2354	3361
Visc @ 40°C	cSt	ASTM D445	35.3	28.4	27.7	27.0



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : VCP438921 **Received** : 17 Jan 2024
Lab Number : 06063941 **Diagnosed** : 18 Jan 2024
Unique Number : 10835323 **Diagnostician** : Wes Davis
Test Package : MOBCE

ALTA EQUIPMENT COMPANY
 5151 DR MARTIN LUTHER KING BLVD
 FORT MYERS, FL
 US 33905
 Contact: TODD LARK
 tlark@altaequipfl.com
 T:
 F: (239)481-3302

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)