



WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>



Area  
**{UNASSIGNED}**  
Machine Id  
**933043**  
Component  
**Transmission (Auto)**  
Fluid  
**PETRO CANADA DuraDrive HD Synthetic 668 (8 GAL)**

**RECOMMENDATION**

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>GFL0107226</b>	GFL0107204	GFL0101202
Sample Date		Client Info		<b>12 Jan 2024</b>	15 Dec 2023	10 Nov 2023
Machine Age	hrs	Client Info		<b>1529</b>	1385	1256
Oil Age	hrs	Client Info		<b>1529</b>	1385	1256
Filter Age	hrs	Client Info		<b>1529</b>	1385	1256
Oil Changed		Client Info		<b>Not Chngd</b>	Not Chngd	Not Chngd
Filter Changed		Client Info		<b>Not Chngd</b>	Not Chngd	Not Chngd
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

**WEAR**

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>325	<b>85</b>	78	28
Chromium	ppm	ASTM D5185m	>2	<b>&lt;1</b>	<1	0
Nickel	ppm	ASTM D5185m	>2	<b>0</b>	<1	0
Titanium	ppm	ASTM D5185m	>3	<b>0</b>	0	0
Silver	ppm	ASTM D5185m	>5	<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m	>75	<b>13</b>	15	7
Lead	ppm	ASTM D5185m	>40	<b>8</b>	6	2
Copper	ppm	ASTM D5185m	>50	<b>16</b>	14	19
Tin	ppm	ASTM D5185m	>10	<b>1</b>	2	1
Vanadium	ppm	ASTM D5185m		<b>0</b>	0	<1
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE

**CONTAMINATION**





There is no indication of any contamination in the fluid.

Silicon	ppm	ASTM D5185m	>20	<b>5</b>	6	7
Potassium	ppm	ASTM D5185m	>20	<b>5</b>	4	1
Water		WC Method	>0.1	<b>NEG</b>	NEG	NEG
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	<b>NEG</b>	NEG	NEG

**FLUID CONDITION**

The condition of the fluid is acceptable for the time in service.

Sodium	ppm	ASTM D5185m		<b>&lt;1</b>	7	7
Boron	ppm	ASTM D5185m		<b>53</b>	46	299
Barium	ppm	ASTM D5185m		<b>4</b>	<1	0
Molybdenum	ppm	ASTM D5185m		<b>0</b>	0	0
Manganese	ppm	ASTM D5185m		<b>1</b>	2	<1
Magnesium	ppm	ASTM D5185m		<b>0</b>	3	0
Calcium	ppm	ASTM D5185m		<b>119</b>	123	222
Phosphorus	ppm	ASTM D5185m		<b>238</b>	219	600
Zinc	ppm	ASTM D5185m		<b>4</b>	35	0
Sulfur	ppm	ASTM D5185m		<b>1718</b>	1653	2253
Visc @ 40°C	cSt	ASTM D445	34	<b>32.1</b>	32.2	32.3



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0107226 **Received** : 18 Jan 2024  
**Lab Number** : 06064644 **Diagnosed** : 19 Jan 2024  
**Unique Number** : 10836026 **Diagnostician** : Wes Davis  
**Test Package** : FLEET

**GFL Environmental - 010 - Stockbridge**  
 1280 Rum Creek Parkway  
 Stockbridge, GA  
 US 30281  
 Contact: JOSHUA TINKER  
 joshuatinker@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:  
F: