



VOLVO

OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Area
[659872]
Machine Id
VOLVO L150H 6945
Component
Transmission (Auto)
Fluid
VOLVO AUTOMATIC TRANSMISSION FLUID AT102 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		VCP437450	VCP432767	VCP408205
Sample Date		Client Info		15 Jan 2024	05 Sep 2023	30 Mar 2023
Machine Age	hrs	Client Info		7995	6908	5534
Oil Age	hrs	Client Info		0	0	0
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Not Changed	Changed	Not Changed
Filter Changed		Client Info		Not Changed	Changed	Not Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>150	36	104	80
Chromium	ppm	ASTM D5185m	>2	<1	<1	<1
Nickel	ppm	ASTM D5185m	>2	0	<1	0
Titanium	ppm	ASTM D5185m	>2	0	0	0
Silver	ppm	ASTM D5185m	>5	0	0	0
Aluminum	ppm	ASTM D5185m	>5	2	2	1
Lead	ppm	ASTM D5185m	>75	0	<1	0
Copper	ppm	ASTM D5185m	>75	6	17	13
Tin	ppm	ASTM D5185m	>4	0	<1	0
Vanadium	ppm	ASTM D5185m		0	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION










There is no indication of any contamination in the fluid.

Silicon	ppm	ASTM D5185m	>20	4	8	8
Potassium	ppm	ASTM D5185m	>20	1	<1	2
Water		WC Method	>0.1	NEG	NEG	NEG
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG

FLUID CONDITION

The condition of the fluid is acceptable for the time in service.

Sodium	ppm	ASTM D5185m		0	5	5
Boron	ppm	ASTM D5185m	187	89	52	55
Barium	ppm	ASTM D5185m	0.0	4	4	6
Molybdenum	ppm	ASTM D5185m	0.0	0	0	<1
Manganese	ppm	ASTM D5185m	0.0	<1	5	5
Magnesium	ppm	ASTM D5185m	6.8	0	3	6
Calcium	ppm	ASTM D5185m	215	71	92	84
Phosphorus	ppm	ASTM D5185m	445	224	200	196
Zinc	ppm	ASTM D5185m	56	0	25	32
Sulfur	ppm	ASTM D5185m	1336	1976	2130	2111
Visc @ 40°C	cSt	ASTM D445	35.3	28.1	27.8	27.9



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : VCP437450 **Received** : 18 Jan 2024
Lab Number : 06064655 **Diagnosed** : 21 Jan 2024
Unique Number : 10836037 **Diagnostician** : Don Baldrige
Test Package : MOB 1

ORANGE COUNTY SOLID WASTE
 5901 YOUNG PINE ROAD
 ORLANDO, FL
 US 32829
 Contact: MICHAEL BEEBE
 michael.beebe@ocfl.net
 T: (407)836-6652
 F: (407)836-6650

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)