



LEAHY-WOLF
Lubricating specialists since 1946

OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Area

TA Machines

Machine Id

Sany SY365 TA745 (S/N SY036MBG80888)

Component

Diesel Engine

Fluid

CITGO 15W40 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		LW0008279	LW0007319	LW0005175
Sample Date		Client Info		16 Jan 2024	31 Aug 2023	21 Jul 2022
Machine Age	hrs	Client Info		4415	4133	3880
Oil Age	hrs	Client Info		4415	4133	3880
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Not Changd	Not Changd	Not Changd
Filter Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	4	12	7
Chromium	ppm	ASTM D5185m	>20	0	<1	<1
Nickel	ppm	ASTM D5185m	>4	0	0	0
Titanium	ppm	ASTM D5185m		<1	6	<1
Silver	ppm	ASTM D5185m	>3	0	0	<1
Aluminum	ppm	ASTM D5185m	>20	2	2	2
Lead	ppm	ASTM D5185m	>40	0	0	<1
Copper	ppm	ASTM D5185m	>330	7	25	2
Tin	ppm	ASTM D5185m	>15	0	<1	0
Vanadium	ppm	ASTM D5185m		<1	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION











There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	5	11	4
Potassium	ppm	ASTM D5185m	>20	<1	4	3
Fuel		WC Method	>5	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.1	0.1	0.1
Nitration	Abs/cm	*ASTM D7624	>20	6.2	8.0	9.9
Sulfation	Abs/.1mm	*ASTM D7415	>30	17.9	19.9	24.1
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		2	8	3
Boron	ppm	ASTM D5185m		35	62	26
Barium	ppm	ASTM D5185m		<1	2	0
Molybdenum	ppm	ASTM D5185m		60	17	19
Manganese	ppm	ASTM D5185m		<1	4	<1
Magnesium	ppm	ASTM D5185m		583	739	669
Calcium	ppm	ASTM D5185m		1546	1495	1510
Phosphorus	ppm	ASTM D5185m		1104	1085	1108
Zinc	ppm	ASTM D5185m		1279	1284	1317
Sulfur	ppm	ASTM D5185m		3533	4161	4193
Oxidation	Abs/.1mm	*ASTM D7414	>25	13.5	14.2	18.3
Base Number (BN)	mg KOH/g	ASTM D2896		8.2	8.8	8.3
Visc @ 100°C	cSt	ASTM D445		13.3	13.5	13.9



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : LW0008279 **Received** : 19 Jan 2024
Lab Number : 06065343 **Diagnosed** : 20 Jan 2024
Unique Number : 10836725 **Diagnostician** : Wes Davis
Test Package : MOB 1 (Additional Tests: TBN)

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

CHICAGO MACHINERY INC

3142 EAST LINCOLN

LYNWOOD, IL

US 60411-7728

Contact: Mike Korblik

mike@chicagomachineryinc.com

T: (708)758-2060

F: