



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
SAFETY LEGEND (S/N 5511879)

Component
Starboard Main Engine

Fluid
CHEVRON DELO 400 MULTIGRADE 15W40 (11 GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		MW0064243	MW0051882	MW0037916
Sample Date		Client Info		11 Jan 2024	08 May 2023	16 Aug 2022
Machine Age	hrs	Client Info		25918	25421	50061
Oil Age	hrs	Client Info		127	256	0
Filter Age	hrs	Client Info		127	256	0
Oil Changed		Client Info		Not Chngd	Changed	Changed
Filter Changed		Client Info		Not Chngd	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>75	4	6	3
Chromium	ppm	ASTM D5185m	>8	<1	<1	0
Nickel	ppm	ASTM D5185m	>2	0	0	0
Titanium	ppm	ASTM D5185m	>3	0	<1	14
Silver	ppm	ASTM D5185m	>2	0	0	<1
Aluminum	ppm	ASTM D5185m	>15	3	<1	<1
Lead	ppm	ASTM D5185m	>18	0	0	0
Copper	ppm	ASTM D5185m	>80	<1	<1	<1
Tin	ppm	ASTM D5185m	>14	0	<1	<1
Vanadium	ppm	ASTM D5185m		<1	0	<1
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>20	6	5	3
Potassium	ppm	ASTM D5185m	>20	<1	<1	2
Fuel		WC Method	>4.0	<1.0	<1.0	<1.0
Water		WC Method	>0.1	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844		0.5	1.1	0.1
Nitration	Abs/cm	*ASTM D7624	>20	6.2	7.7	7.3
Sulfation	Abs/.1mm	*ASTM D7415	>30	22.7	24.5	19.5
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m	>75	2	4	0
Boron	ppm	ASTM D5185m		324	280	114
Barium	ppm	ASTM D5185m		<1	0	0
Molybdenum	ppm	ASTM D5185m		124	124	32
Manganese	ppm	ASTM D5185m		<1	<1	<1
Magnesium	ppm	ASTM D5185m		726	628	707
Calcium	ppm	ASTM D5185m		1573	1671	1577
Phosphorus	ppm	ASTM D5185m	1360	775	721	703
Zinc	ppm	ASTM D5185m	1480	927	862	802
Sulfur	ppm	ASTM D5185m		2774	2731	3037
Oxidation	Abs/.1mm	*ASTM D7414	>25	15.6	16.6	13.4
Base Number (BN)	mg KOH/g	ASTM D2896	12.2	8.5	8.2	9.7
Visc @ 100°C	cSt	ASTM D445	15.1	13.0	13.3	14.7



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : MW0064243 **Received** : 19 Jan 2024
Lab Number : 06065359 **Diagnosed** : 22 Jan 2024
Unique Number : 10836741 **Diagnostician** : Wes Davis
Test Package : MAR 2

MARITIME COMPANY
 3802 PORT RIVER RD
 PASCAGOULA, MS
 US 39567
 Contact: TERRY SCUDDER
 terry.scudder@signetmaritime.com
 T:
 F: (228)769-0629

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)