



|                 |               |
|-----------------|---------------|
| WEAR            | <b>NORMAL</b> |
| CONTAMINATION   | <b>NORMAL</b> |
| FLUID CONDITION | <b>NORMAL</b> |

Machine Id  
**SAFETY LEGEND (S/N CC-4670-09)**

Component  
**Port Genset**

Fluid  
**CHEVRON URSA SUPER PLUS 40 (4 GAL)**

**RECOMMENDATION**

Resample at the next service interval to monitor.

| Test           | UOM | Method      | Limit/Abn | Current            | History1    | History2    |
|----------------|-----|-------------|-----------|--------------------|-------------|-------------|
| Sample Number  |     | Client Info |           | <b>MW0064236</b>   | MW0051881   | MW0037955   |
| Sample Date    |     | Client Info |           | <b>11 Jan 2024</b> | 08 May 2023 | 16 Aug 2022 |
| Machine Age    | hrs | Client Info |           | <b>2728</b>        | 2420        | 29415       |
| Oil Age        | hrs | Client Info |           | <b>36</b>          | 205         | 0           |
| Filter Age     | hrs | Client Info |           | <b>36</b>          | 205         | 0           |
| Oil Changed    |     | Client Info |           | <b>Not Changd</b>  | Changed     | Changed     |
| Filter Changed |     | Client Info |           | <b>Not Changd</b>  | Changed     | Changed     |
| Sample Status  |     |             |           | <b>NORMAL</b>      | NORMAL      | NORMAL      |

**WEAR**

All component wear rates are normal.

|              |        |             |      |              |      |      |
|--------------|--------|-------------|------|--------------|------|------|
| Iron         | ppm    | ASTM D5185m | >50  | <b>21</b>    | 21   | 3    |
| Chromium     | ppm    | ASTM D5185m | >4   | <b>&lt;1</b> | 0    | 0    |
| Nickel       | ppm    | ASTM D5185m | >2   | <b>0</b>     | 0    | 0    |
| Titanium     | ppm    | ASTM D5185m |      | <b>0</b>     | <1   | 14   |
| Silver       | ppm    | ASTM D5185m | >5   | <b>0</b>     | 0    | <1   |
| Aluminum     | ppm    | ASTM D5185m | >12  | <b>&lt;1</b> | <1   | <1   |
| Lead         | ppm    | ASTM D5185m | >17  | <b>&lt;1</b> | 1    | <1   |
| Copper       | ppm    | ASTM D5185m | >70  | <b>4</b>     | 7    | 0    |
| Tin          | ppm    | ASTM D5185m | >15  | <b>3</b>     | 4    | <1   |
| Vanadium     | ppm    | ASTM D5185m |      | <b>&lt;1</b> | 0    | <1   |
| White Metal  | scalar | *Visual     | NONE | <b>NONE</b>  | NONE | NONE |
| Yellow Metal | scalar | *Visual     | NONE | <b>NONE</b>  | NONE | NONE |

**CONTAMINATION**







There is no indication of any contamination in the oil.

|                  |          |             |       |                |       |       |
|------------------|----------|-------------|-------|----------------|-------|-------|
| Silicon          | ppm      | ASTM D5185m | >25   | <b>6</b>       | 7     | 3     |
| Potassium        | ppm      | ASTM D5185m | >20   | <b>0</b>       | 0     | 1     |
| Fuel             |          | WC Method   | >4.0  | <b>&lt;1.0</b> | <1.0  | <1.0  |
| Water            |          | WC Method   | >0.1  | <b>NEG</b>     | NEG   | NEG   |
| Glycol           |          | WC Method   |       | <b>NEG</b>     | NEG   | NEG   |
| Soot %           | %        | *ASTM D7844 |       | <b>0.1</b>     | 0.1   | 0.1   |
| Nitration        | Abs/cm   | *ASTM D7624 | >20   | <b>3.7</b>     | 4.1   | 7.5   |
| Sulfation        | Abs/.1mm | *ASTM D7415 | >30   | <b>15.2</b>    | 16.3  | 19.6  |
| Silt             | scalar   | *Visual     | NONE  | <b>NONE</b>    | NONE  | NONE  |
| Debris           | scalar   | *Visual     | NONE  | <b>NONE</b>    | NONE  | NONE  |
| Sand/Dirt        | scalar   | *Visual     | NONE  | <b>NONE</b>    | NONE  | NONE  |
| Appearance       | scalar   | *Visual     | NORML | <b>NORML</b>   | NORML | NORML |
| Odor             | scalar   | *Visual     | NORML | <b>NORML</b>   | NORML | NORML |
| Emulsified Water | scalar   | *Visual     | >0.1  | <b>NEG</b>     | NEG   | NEG   |

**FLUID CONDITION**

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

|                  |          |             |      |              |      |      |
|------------------|----------|-------------|------|--------------|------|------|
| Sodium           | ppm      | ASTM D5185m |      | <b>4</b>     | 3    | 0    |
| Boron            | ppm      | ASTM D5185m |      | <b>293</b>   | 328  | 114  |
| Barium           | ppm      | ASTM D5185m |      | <b>0</b>     | 0    | 0    |
| Molybdenum       | ppm      | ASTM D5185m |      | <b>39</b>    | 50   | 32   |
| Manganese        | ppm      | ASTM D5185m |      | <b>&lt;1</b> | <1   | <1   |
| Magnesium        | ppm      | ASTM D5185m |      | <b>104</b>   | 192  | 723  |
| Calcium          | ppm      | ASTM D5185m |      | <b>2284</b>  | 1876 | 1610 |
| Phosphorus       | ppm      | ASTM D5185m | 1000 | <b>741</b>   | 755  | 703  |
| Zinc             | ppm      | ASTM D5185m | 1090 | <b>873</b>   | 886  | 811  |
| Sulfur           | ppm      | ASTM D5185m |      | <b>3033</b>  | 3095 | 3053 |
| Oxidation        | Abs/.1mm | *ASTM D7414 | >25  | <b>7.1</b>   | 9.4  | 14.0 |
| Base Number (BN) | mg KOH/g | ASTM D2896  | 7.4  | <b>6.2</b>   | 6.6  | 9.6  |
| Visc @ 100°C     | cSt      | ASTM D445   | 14.7 | <b>13.5</b>  | 12.9 | 14.5 |



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : MW0064236 **Received** : 19 Jan 2024  
**Lab Number** : 06065360 **Diagnosed** : 22 Jan 2024  
**Unique Number** : 10836742 **Diagnostician** : Wes Davis  
**Test Package** : MAR 2

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

**MARITIME COMPANY**  
 3802 PORT RIVER RD  
 PASCAGOULA, MS  
 US 39567

Contact: TERRY SCUDDER  
 terry.scudder@signetmaritime.com

T:  
 F: (228)769-0629