



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Area
(UA22462)
Machine Id
2270
Component
Diesel Engine
Fluid
PETRO CANADA DURON SHP 15W40 (--- QTS)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		GFL0103889	GFL0060148	GFL0044087
Sample Date		Client Info		15 Jan 2024	24 Oct 2022	29 Apr 2022
Machine Age	mls	Client Info		426664	426664	426664
Oil Age	mls	Client Info		426664	34449	34001
Filter Age	mls	Client Info		0	606	158
Oil Changed		Client Info		N/A	Changed	Not Changd
Filter Changed		Client Info		N/A	Changed	Not Changd
Sample Status				NORMAL	ATTENTION	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>120	9	▲ 71	12
Chromium	ppm	ASTM D5185m	>20	<1	1	<1
Nickel	ppm	ASTM D5185m	>5	0	0	<1
Titanium	ppm	ASTM D5185m	>2	0	<1	<1
Silver	ppm	ASTM D5185m	>2	0	0	<1
Aluminum	ppm	ASTM D5185m	>20	4	3	<1
Lead	ppm	ASTM D5185m	>40	0	7	3
Copper	ppm	ASTM D5185m	>330	<1	16	6
Tin	ppm	ASTM D5185m	>15	0	2	1
Vanadium	ppm	ASTM D5185m		<1	<1	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	6	4	2
Potassium	ppm	ASTM D5185m	>20	<1	<1	0
Fuel		WC Method	>3.0	<1.0	<1.0	2.4
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>4	0	3.6	0.8
Nitration	Abs/cm	*ASTM D7624	>20	8.5	10.1	5.8
Sulfation	Abs/.1mm	*ASTM D7415	>30	19.5	25.4	19.3
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		3	1	<1
Boron	ppm	ASTM D5185m	0	24	0	0
Barium	ppm	ASTM D5185m	0	<1	0	0
Molybdenum	ppm	ASTM D5185m	60	47	54	58
Manganese	ppm	ASTM D5185m	0	<1	1	<1
Magnesium	ppm	ASTM D5185m	1010	580	839	897
Calcium	ppm	ASTM D5185m	1070	1538	1046	1093
Phosphorus	ppm	ASTM D5185m	1150	820	919	1044
Zinc	ppm	ASTM D5185m	1270	993	1195	1243
Sulfur	ppm	ASTM D5185m	2060	2584	3147	2906
Oxidation	Abs/.1mm	*ASTM D7414	>25	16.3	15.0	13.3
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	7.2	8.9	9.8
Visc @ 100°C	cSt	ASTM D445	15.4	14.7	14.2	13.7



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0103889 **Recieved** : 19 Jan 2024
Lab Number : 06065382 **Diagnosed** : 22 Jan 2024
Unique Number : 10836764 **Diagnostician** : Don Baldrige
Test Package : FLEET

GFL Environmental - 045 - Tidewater
 3821 Cook Blvd.
 Chesapeake, VA
 US 23323
 Contact: ELVIN RODRIGUEZ
 elvinrodriguez@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: