



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Area
Store 2 - Beaver
 Machine Id
JOHN DEERE 1T0325GKPKJ359273
 Component
Diesel Engine
 Fluid
SHELL 15W40 (--- QTS)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		LEC0042921	LEC0043844	LEC0037289
Sample Date		Client Info		15 Dec 2023	28 Jul 2023	09 Mar 2023
Machine Age	hrs	Client Info		1426	1216	1017
Oil Age	hrs	Client Info		409	199	409
Filter Age	hrs	Client Info		409	199	409
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	NORMAL	ABNORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>51	15	14	24
Chromium	ppm	ASTM D5185m	>11	<1	<1	<1
Nickel	ppm	ASTM D5185m	>5	0	0	0
Titanium	ppm	ASTM D5185m		0	<1	<1
Silver	ppm	ASTM D5185m	>3	0	<1	<1
Aluminum	ppm	ASTM D5185m	>31	5	4	6
Lead	ppm	ASTM D5185m	>26	0	<1	0
Copper	ppm	ASTM D5185m	>26	2	6	▲ 38
Tin	ppm	ASTM D5185m	>4	<1	<1	<1
Vanadium	ppm	ASTM D5185m		<1	<1	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>120	12	7	14
Potassium	ppm	ASTM D5185m	>20	2	5	0
Fuel		WC Method	>2.1	<1.0	<1.0	<1.0
Water		WC Method	>0.21	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.4	0.4	0.6
Nitration	Abs/cm	*ASTM D7624	>20	8.2	7.4	9.4
Sulfation	Abs/.1mm	*ASTM D7415	>30	21.2	20.2	23.8
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.21	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m	>150	2	3	4
Boron	ppm	ASTM D5185m		236	120	154
Barium	ppm	ASTM D5185m		<1	0	0
Molybdenum	ppm	ASTM D5185m		215	45	182
Manganese	ppm	ASTM D5185m		<1	<1	1
Magnesium	ppm	ASTM D5185m		743	277	568
Calcium	ppm	ASTM D5185m		1665	1763	1222
Phosphorus	ppm	ASTM D5185m		974	867	671
Zinc	ppm	ASTM D5185m		1210	1093	819
Sulfur	ppm	ASTM D5185m		3441	3484	2400
Oxidation	Abs/.1mm	*ASTM D7414	>25	16.2	16.1	18.9
Base Number (BN)	mg KOH/g	ASTM D2896		8.8	8.2	8.6
Visc @ 100°C	cSt	ASTM D445		14.2	14.4	13.1



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : LEC0042921 **Received** : 19 Jan 2024
Lab Number : 06065453 **Diagnosed** : 22 Jan 2024
Unique Number : 10836835 **Diagnostician** : Wes Davis
Test Package : CONST (Additional Tests: TBN)

C. J. HUGHES CONSTRUCTION
 PO BOX 7305
 HUNTINGTON, WV
 US 25776
 Contact: DEWEY SHEPPARD
 dsheppard@cjhughes.com
 T: (304)522-3868
 F: (304)743-5449

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)