



WEAR CHECK

OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	SEVERE
FLUID CONDITION	ABNORMAL

Machine Id

721

Component

Diesel Engine

Fluid

PETRO CANADA DURON SHP 15W40 (--- QTS)

RECOMMENDATION

We advise that you check the fuel injection system. The oil change at the time of sampling has been noted. We recommend an early resample to monitor this condition. Please specify the component make and model with your next sample.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		WC0817199	WC0773735	WC0773637
Sample Date		Client Info		17 Jan 2024	19 Sep 2023	07 Jul 2023
Machine Age	hrs	Client Info		20795	20544	0
Oil Age	hrs	Client Info		0	0	0
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				SEVERE	ABNORMAL	ABNORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	11	5	12
Chromium	ppm	ASTM D5185m	>20	<1	<1	<1
Nickel	ppm	ASTM D5185m	>4	0	0	0
Titanium	ppm	ASTM D5185m		<1	<1	<1
Silver	ppm	ASTM D5185m	>3	0	0	0
Aluminum	ppm	ASTM D5185m	>20	<1	0	2
Lead	ppm	ASTM D5185m	>40	0	<1	<1
Copper	ppm	ASTM D5185m	>330	<1	<1	1
Tin	ppm	ASTM D5185m	>15	0	<1	0
Vanadium	ppm	ASTM D5185m		0	<1	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION








There is a high amount of fuel present in the oil. Tests confirm the presence of fuel in the oil.

Silicon	ppm	ASTM D5185m	>25	3	3	3
Potassium	ppm	ASTM D5185m	>20	12	<1	5
Fuel	%	ASTM D3524	>5	8.6	6.7	5.6
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.5	0.5	0.5
Nitration	Abs/cm	*ASTM D7624	>20	8.6	8.0	8.4
Sulfation	Abs/.1mm	*ASTM D7415	>30	20.7	20.4	20.6
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. Fuel is present in the oil and is lowering the viscosity. The oil is no longer serviceable due to the presence of contaminants.

Sodium	ppm	ASTM D5185m		3	<1	0
Boron	ppm	ASTM D5185m	0	1	<1	<1
Barium	ppm	ASTM D5185m	0	0	0	0
Molybdenum	ppm	ASTM D5185m	60	54	59	57
Manganese	ppm	ASTM D5185m	0	0	<1	<1
Magnesium	ppm	ASTM D5185m	1010	880	1007	844
Calcium	ppm	ASTM D5185m	1070	1003	1090	1025
Phosphorus	ppm	ASTM D5185m	1150	933	993	962
Zinc	ppm	ASTM D5185m	1270	1116	1245	1161
Sulfur	ppm	ASTM D5185m	2060	2815	3643	2929
Oxidation	Abs/.1mm	*ASTM D7414	>25	19.6	18.5	17.9
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	8.2	8.0	8.5
Visc @ 100°C	cSt	ASTM D445	15.4	11.4	14.0	12.2



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : WC0817199 **Received** : 30 Jan 2024
Lab Number : 06073566 **Diagnosed** : 31 Jan 2024
Unique Number : 10850243 **Diagnostician** : Wes Davis
Test Package : FLEET (Additional Tests: PercentFuel)

AREA TRANSPORTATION AUTHORITY
 44 TRANSPORTATION CENTER
 JOHNSONBURG, PA
 US 15845
 Contact: J SCHLODER
 jschloder@rideata.com

Certificate L2367
 To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)