



WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>

Machine Id  
**921047-260381**

Component  
**Diesel Engine**

Fluid  
**PETRO CANADA DURON SHP 15W40 (--- GAL)**

**RECOMMENDATION**

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>GFL0108150</b>	GFL0102487	GFL0102436
Sample Date		Client Info		<b>19 Jan 2024</b>	28 Dec 2023	19 Dec 2023
Machine Age	hrs	Client Info		<b>7043</b>	6903	6851
Oil Age	hrs	Client Info		<b>0</b>	0	0
Filter Age	hrs	Client Info		<b>0</b>	0	0
Oil Changed		Client Info		<b>Not Changd</b>	Changed	N/A
Filter Changed		Client Info		<b>Not Changd</b>	Changed	N/A
Sample Status				<b>NORMAL</b>	ATTENTION	ATTENTION

**WEAR**

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	<b>3</b>	15	14
Chromium	ppm	ASTM D5185m	>20	<b>0</b>	1	<1
Nickel	ppm	ASTM D5185m	>4	<b>&lt;1</b>	0	<1
Titanium	ppm	ASTM D5185m		<b>0</b>	0	0
Silver	ppm	ASTM D5185m	>3	<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m	>20	<b>3</b>	4	5
Lead	ppm	ASTM D5185m	>40	<b>0</b>	<1	<1
Copper	ppm	ASTM D5185m	>330	<b>0</b>	2	2
Tin	ppm	ASTM D5185m	>15	<b>&lt;1</b>	<1	<1
Vanadium	ppm	ASTM D5185m		<b>0</b>	0	0
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	LIGHT
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE

**CONTAMINATION**







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	<b>3</b>	6	7
Potassium	ppm	ASTM D5185m	>20	<b>1</b>	5	5
Fuel		WC Method	>5	<b>&lt;1.0</b>	<1.0	<1.0
Water		WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol		WC Method		<b>NEG</b>	NEG	NEG
Soot %	%	*ASTM D7844	>3	<b>0.3</b>	0.7	0.5
Nitration	Abs/cm	*ASTM D7624	>20	<b>5.2</b>	8.0	6.9
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>18.2</b>	20.1	20.1
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	<b>NEG</b>	NEG	NEG

**FLUID CONDITION**

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		<b>16</b>	▲ 154	▲ 149
Boron	ppm	ASTM D5185m	0	<b>3</b>	4	6
Barium	ppm	ASTM D5185m	0	<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m	60	<b>55</b>	61	65
Manganese	ppm	ASTM D5185m	0	<b>&lt;1</b>	<1	<1
Magnesium	ppm	ASTM D5185m	1010	<b>898</b>	913	990
Calcium	ppm	ASTM D5185m	1070	<b>979</b>	1032	1093
Phosphorus	ppm	ASTM D5185m	1150	<b>1015</b>	1038	1131
Zinc	ppm	ASTM D5185m	1270	<b>1212</b>	1181	1373
Sulfur	ppm	ASTM D5185m	2060	<b>2957</b>	2918	3300
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>13.2</b>	15.1	15.1
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	<b>8.8</b>	8.2	8.1
Visc @ 100°C	cSt	ASTM D445	15.4	<b>14.2</b>	13.9	13.8



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0108150 **Received** : 30 Jan 2024  
**Lab Number** : 06073622 **Diagnosed** : 30 Jan 2024  
**Unique Number** : 10850299 **Diagnostician** : Wes Davis  
**Test Package** : FLEET

**GFL Environmental - 837 - Harrison TS**  
 22820 S State Route 291  
 Harrisonville, MO  
 US 64701  
 Contact: BRYAN SWANSON  
 bryanswanson@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:  
F: