



PacLease

OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
857-4727

Component
Diesel Engine

Fluid
CHEVRON DELO 400 XLE 10W30 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor. Please specify the component make and model with your next sample.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		RPL0014859	RPL0010170	---
Sample Date		Client Info		21 Dec 2023	28 Jul 2023	---
Machine Age	mls	Client Info		138187	110110	---
Oil Age	mls	Client Info		28077	31303	---
Filter Age	mls	Client Info		28077	31303	---
Oil Changed		Client Info		Changed	Changed	---
Filter Changed		Client Info		Changed	Changed	---
Sample Status				NORMAL	NORMAL	---

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	40	55	---
Chromium	ppm	ASTM D5185m	>20	2	2	---
Nickel	ppm	ASTM D5185m	>4	<1	<1	---
Titanium	ppm	ASTM D5185m		<1	<1	---
Silver	ppm	ASTM D5185m	>3	0	0	---
Aluminum	ppm	ASTM D5185m	>20	19	14	---
Lead	ppm	ASTM D5185m	>40	3	2	---
Copper	ppm	ASTM D5185m	>330	4	4	---
Tin	ppm	ASTM D5185m	>15	1	2	---
Vanadium	ppm	ASTM D5185m		<1	0	---
White Metal	scalar	*Visual	NONE	NONE	NONE	---
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	---

CONTAMINATION







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	12	12	---
Potassium	ppm	ASTM D5185m	>20	31	47	---
Fuel		WC Method	>5	<1.0	<1.0	---
Water		WC Method	>0.2	NEG	NEG	---
Glycol		WC Method		NEG	NEG	---
Soot %	%	*ASTM D7844	>3	1.7	2	---
Nitration	Abs/cm	*ASTM D7624	>20	12.3	11.9	---
Sulfation	Abs/.1mm	*ASTM D7415	>30	28.3	29.8	---
Silt	scalar	*Visual	NONE	NONE	NONE	---
Debris	scalar	*Visual	NONE	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	---

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		3	10	---
Boron	ppm	ASTM D5185m		21	17	---
Barium	ppm	ASTM D5185m		0	0	---
Molybdenum	ppm	ASTM D5185m		14	12	---
Manganese	ppm	ASTM D5185m		<1	1	---
Magnesium	ppm	ASTM D5185m		831	787	---
Calcium	ppm	ASTM D5185m	2900	1695	1636	---
Phosphorus	ppm	ASTM D5185m	1100	847	774	---
Zinc	ppm	ASTM D5185m	1200	1043	930	---
Sulfur	ppm	ASTM D5185m	4000	3618	3562	---
Oxidation	Abs/.1mm	*ASTM D7414	>25	22.8	23.3	---
Base Number (BN)	mg KOH/g	ASTM D2896	10.3	6.0	4.6	---
Visc @ 100°C	cSt	ASTM D445	11.9	12.4	12.2	---



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : RPL0014859 **Received** : 30 Jan 2024
Lab Number : 06073702 **Diagnosed** : 31 Jan 2024
Unique Number : 10850379 **Diagnostician** : Wes Davis
Test Package : FLEET

RTL PACLEASE - 7001 - Houston
 6300 N. Loop East
 Houston, TX
 US 77026
 Contact: RODNEY BRIGGS
 briggsr@rushenterprises.com
 T:
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)