



TRAAP

Texas Refinery Advanced Analysis Program

OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
CHEVROLET T-6E
 Component
Gasoline Engine
 Fluid
TRC MOLY PRO-SPEC MOTOR 10W30 (8 QTS)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		TR06074154	TR06006540	TR05656892
Sample Date		Client Info		02 Jan 2024	06 Nov 2023	20 Sep 2022
Machine Age	mls	Client Info		148092	142518	97539
Oil Age	mls	Client Info		0	0	0
Filter Age	mls	Client Info		0	0	0
Oil Changed		Client Info		Not Changd	Not Changd	Not Changd
Filter Changed		Client Info		Not Changd	Changed	Not Changd
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>150	11	8	5
Chromium	ppm	ASTM D5185m	>20	<1	0	<1
Nickel	ppm	ASTM D5185m	>5	0	0	0
Titanium	ppm	ASTM D5185m		<1	0	<1
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>40	3	2	2
Lead	ppm	ASTM D5185m	>50	<1	<1	<1
Copper	ppm	ASTM D5185m	>155	6	9	4
Tin	ppm	ASTM D5185m	>10	<1	0	0
Vanadium	ppm	ASTM D5185m		0	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION











There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>30	13	13	12
Potassium	ppm	ASTM D5185m	>20	4	2	<1
Fuel		WC Method	>4.0	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844		0	0.1	0.1
Nitration	Abs/cm	*ASTM D7624	>20	18.6	17.1	13.3
Sulfation	Abs/.1mm	*ASTM D7415	>30	31.0	29.4	26.5
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m	>400	6	9	2
Boron	ppm	ASTM D5185m		0	0	0
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		<1	1	1
Manganese	ppm	ASTM D5185m		2	<1	1
Magnesium	ppm	ASTM D5185m		17	37	23
Calcium	ppm	ASTM D5185m		3912	3921	4105
Phosphorus	ppm	ASTM D5185m		763	865	819
Zinc	ppm	ASTM D5185m		994	1053	1026
Sulfur	ppm	ASTM D5185m		3887	3945	4584
Oxidation	Abs/.1mm	*ASTM D7414	>25	26.2	23.7	18.5
Base Number (BN)	mg KOH/g	ASTM D2896		7.83	8.64	9.62
Visc @ 100°C	cSt	ASTM D445	12.0	11.4	11.9	11.8



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : TR06074154 **Received** : 30 Jan 2024
Lab Number : 06074154 **Diagnosed** : 31 Jan 2024
Unique Number : 10856245 **Diagnostician** : Sean Felton
Test Package : MOB 2

WELD COUNTY SCHOOL DISTRICT
 110 N 8TH ST
 WINDSOR, CO
 US 80550
 Contact: JAMES WEST
 james@sellsoil.com
 T: (720)425-9923
 F: x:

Certificate L2367
 To discuss this sample report, contact Customer Service at 1-800-827-0711.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)