

#### Machine Id HC-2205 Component Diesel Fuel Fluid {not provided} (--- GAL)

# RECOMMENDATION

We advise that you check for the source of water (DEF) entry. Recommend drain fuel if not already done and flush before refilling with fuel.

### CORROSION

All metal levels are normal indicating no corrosion in the system.

\_\_\_\_\_


## CONTAMINANTS

**FUEL CONDITION** 

Excessive free water present. Testing indicates DEF.

| h | Test          | UOM | Method      | Limit/Abn | Current      | History1    | History2    |
|---|---------------|-----|-------------|-----------|--------------|-------------|-------------|
|   | Sample Number |     | Client Info |           | WC0873366    | WC0873313   | WC0720697   |
|   | Sample Date   |     | Client Info |           | 10 Jan 2024  | 10 Jan 2024 | 20 Sep 2022 |
|   | Machine Age   | hrs | Client Info |           | 7825         | 7825        | 6950        |
|   | Sample Status |     |             |           | ABNORMAL     | NORMAL      | NORMAL      |
|   | Aluminum      | ppm | ASTM D5185m | <0.1      | <1           | 0           | 0           |
|   | Nickel        | ppm | ASTM D5185m | <0.1      | <1           | <1          | 0           |
|   | Lead          | ppm | ASTM D5185m | <0.1      | 0            | 0           | 0           |
|   | Vanadium      | ppm | ASTM D5185m | <0.1      | 0            | 0           | 0           |
|   | Iron          | ppm | ASTM D5185m | <0.1      | 0            | 0           | 0           |
|   | Silicon       | ppm | ASTM D5185m | <1.0      | <1           | 0           | 0           |
|   | Sodium        | ppm | ASTM D5185m | <0.1      | <1           | <1          | 0           |
|   | Potassium     | ppm | ASTM D5185m | <0.1      | 0            | 0           | 0           |
|   | Water         | %   | ASTM D6304  | <0.05     | 0.003        | 0.004       | 0.003       |
|   | ppm Water     | ppm | ASTM D6304  | <500      | 39           | 43          | 28.8        |
|   | Calcium       | ppm | ASTM D5185m | <0.1      | 1            | 1           | <1          |
|   | Magnesium     | ppm | ASTM D5185m | <0.1      | <1           | <1          | 0           |
|   | Phosphorus    | ppm | ASTM D5185m | <0.1      | 0            | 0           | 2           |
|   | Zinc          | ppm | ASTM D5185m | <0.1      | 0            | 0           | 0           |
|   | Visc @ 40°C   | cSt | ASTM D445   |           | <b>1</b> .54 | 2.88        | 2.46        |
|   | Sulfur        | ppm | ASTM D5185m |           | 0            | 0           | 13          |
|   |               |     |             |           |              |             |             |

The fuel is no longer serviceable due to the presence of contaminants.



#### Pensky-Martens Flash Point (°C)

