



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Area

BARGE TRANSPORTATION

Machine Id

KEITH DOSS - SME

Component

Port Main Engine

Fluid

PETRO CANADA DURON HP 15W40 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		KFS0002654	KFS0002660	KFS0002889
Sample Date		Client Info		16 Dec 2023	19 Sep 2023	12 Apr 2023
Machine Age	hrs	Client Info		0	0	0
Oil Age	hrs	Client Info		478	500	500
Filter Age	hrs	Client Info		478	500	500
Oil Changed		Client Info		Not Changd	Not Changd	Not Changd
Filter Changed		Client Info		Not Changd	N/A	Not Changd
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>75	0	0	2
Chromium	ppm	ASTM D5185m	>8	0	<1	<1
Nickel	ppm	ASTM D5185m	>2	1	<1	1
Titanium	ppm	ASTM D5185m	>3	0	0	0
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>15	1	<1	0
Lead	ppm	ASTM D5185m	>18	0	<1	<1
Copper	ppm	ASTM D5185m	>80	0	1	2
Tin	ppm	ASTM D5185m	>14	<1	0	<1
Vanadium	ppm	ASTM D5185m		0	<1	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>20	2	2	2
Potassium	ppm	ASTM D5185m	>20	<1	1	<1
Fuel		WC Method	>4.0	<1.0	<1.0	<1.0
Water		WC Method	>0.1	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844		0	0.1	0
Nitration	Abs/cm	*ASTM D7624	>20	5.0	5.6	5.5
Sulfation	Abs/.1mm	*ASTM D7415	>30	17.6	17.4	17.9
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m	>75	<1	<1	1
Boron	ppm	ASTM D5185m		6	3	5
Barium	ppm	ASTM D5185m		0	0	2
Molybdenum	ppm	ASTM D5185m		58	55	61
Manganese	ppm	ASTM D5185m		<1	0	0
Magnesium	ppm	ASTM D5185m		918	945	945
Calcium	ppm	ASTM D5185m		990	1007	1077
Phosphorus	ppm	ASTM D5185m		1004	1037	1051
Zinc	ppm	ASTM D5185m		1227	1218	1229
Sulfur	ppm	ASTM D5185m		3043	3157	3225
Oxidation	Abs/.1mm	*ASTM D7414	>25	13.3	13.6	13.9
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	8.5	9.3	9.91
Visc @ 100°C	cSt	ASTM D445	15.6	13.8	13.6	13.6



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : KFS0002654 **Received** : 30 Jan 2024
Lab Number : 06074341 **Diagnosed** : 31 Jan 2024
Unique Number : 10856432 **Diagnostician** : Wes Davis
Test Package : FLEET

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

M/V KEITH DOSS
 3501 STARLITE DR
 PADUCAH, KY
 US 42003
 Contact: KEITH DOSS
 kdoss@hfline.com

T:
 F: