



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
729068-362012
 Component
Natural Gas Engine
 Fluid
PETRO CANADA DURON GEO LD 15W40 (--- LTR)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		GFL0096003	GFL0071713	GFL0071753
Sample Date		Client Info		29 Jan 2024	05 Jul 2023	26 May 2023
Machine Age	hrs	Client Info		12356	10951	10672
Oil Age	hrs	Client Info		600	300	600
Filter Age	hrs	Client Info		600	300	600
Oil Changed		Client Info		Changed	Oil Added	Oil Added
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>50	9	7	3
Chromium	ppm	ASTM D5185m	>4	<1	<1	<1
Nickel	ppm	ASTM D5185m	>2	1	0	<1
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m	>3	0	0	0
Aluminum	ppm	ASTM D5185m	>9	3	2	<1
Lead	ppm	ASTM D5185m	>30	3	1	2
Copper	ppm	ASTM D5185m	>35	<1	1	0
Tin	ppm	ASTM D5185m	>4	<1	<1	<1
Vanadium	ppm	ASTM D5185m		<1	0	<1
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>+100	3	3	6
Potassium	ppm	ASTM D5185m	>20	<1	2	2
Water		WC Method	>0.1	NEG	NEG	NEG
Soot %	%	*ASTM D7844		0	0.1	0
Nitration	Abs/cm	*ASTM D7624	>20	10.1	10.4	8.6
Sulfation	Abs/.1mm	*ASTM D7415	>30	22.8	20.6	20.8
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		8	7	4
Boron	ppm	ASTM D5185m	50	18	14	28
Barium	ppm	ASTM D5185m	5	0	0	0
Molybdenum	ppm	ASTM D5185m	50	52	52	51
Manganese	ppm	ASTM D5185m	0	<1	<1	<1
Magnesium	ppm	ASTM D5185m	560	572	566	535
Calcium	ppm	ASTM D5185m	1510	1510	1599	1554
Phosphorus	ppm	ASTM D5185m	780	783	777	781
Zinc	ppm	ASTM D5185m	870	1015	1026	992
Sulfur	ppm	ASTM D5185m	2040	2464	3089	3080
Oxidation	Abs/.1mm	*ASTM D7414	>25	18.4	17.4	17.2
Base Number (BN)	mg KOH/g	ASTM D2896	10.2	4.7	6.1	7.1
Visc @ 100°C	cSt	ASTM D445	15.1	14.3	14.5	14.6



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0096003 **Received** : 30 Jan 2024
Lab Number : 06074437 **Diagnosed** : 01 Feb 2024
Unique Number : 10856528 **Diagnostician** : Jonathan Hester
Test Package : FLEET

GFL Environmental - 883 - Orange City
 1378 South Volusia Ave
 Orange City, FL
 US 32763
 Contact: Kenneth Pearce
 kpearce@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: