



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Area
JIM BONAHOOM [GARRETT 17517]

Machine Id
VOLVO PENTA A237010

Component
Port Diesel Engine

Fluid
VOLVO VDS-4.5 Premium Motor Oil 15W40 (5 GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		VPA055745	VPA034011	VPA040884
Sample Date		Client Info		24 Jan 2024	01 Dec 2022	15 Mar 2022
Machine Age	hrs	Client Info		940	900	767
Oil Age	hrs	Client Info		40	56	0
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>80	7	10	11
Chromium	ppm	ASTM D5185m	>6	0	2	<1
Nickel	ppm	ASTM D5185m	>2	<1	2	<1
Titanium	ppm	ASTM D5185m	>2	0	2	0
Silver	ppm	ASTM D5185m	>2	<1	2	0
Aluminum	ppm	ASTM D5185m	>20	2	4	6
Lead	ppm	ASTM D5185m	>95	2	<1	2
Copper	ppm	ASTM D5185m	>85	2	4	4
Tin	ppm	ASTM D5185m	>9	<1	2	<1
Vanadium	ppm	ASTM D5185m		<1	2	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION











There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	7	10	6
Potassium	ppm	ASTM D5185m	>20	3	7	1
Fuel		WC Method	>4.0	<1.0	<1.0	<1.0
Water		WC Method	>0.1	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844		0.1	0.2	0.4
Nitration	Abs/cm	*ASTM D7624	>20	5.2	5.7	10.6
Sulfation	Abs/.1mm	*ASTM D7415	>30	18.9	17.3	21.6
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185m		1	2	1
Boron	ppm	ASTM D5185m		6	17	30
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		60	60	53
Manganese	ppm	ASTM D5185m		<1	2	<1
Magnesium	ppm	ASTM D5185m		989	1011	885
Calcium	ppm	ASTM D5185m		1008	1159	1220
Phosphorus	ppm	ASTM D5185m		1153	1070	1077
Zinc	ppm	ASTM D5185m		1343	1343	1267
Sulfur	ppm	ASTM D5185m		3560	3618	3034
Oxidation	Abs/.1mm	*ASTM D7414	>25	14.3	13.8	18.0
Base Number (BN)	mg KOH/g	ASTM D2896		9.9	9.1	10.0
Visc @ 100°C	cSt	ASTM D445		13.2	13.5	13.7



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : VPA055745 **Received** : 31 Jan 2024
Lab Number : 06075451 **Diagnosed** : 01 Feb 2024
Unique Number : 10857542 **Diagnostician** : Don Baldrige
Test Package : MOB 1 (Additional Tests: TBN)

Bayview Yachtcrafters Inc
 31785 S. River Road
 HARRISON TOWNSHIP, MI
 US 48045

Contact: Shawn Robertson
 bayviewyachtcrafters@comcast.net

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: