



WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>

Machine Id  
**GARRON L SNEED (S/N 560609)**  
Component  
**Starboard Reduction Gear**  
Fluid  
**MOBIL MOBILGEAR 600 XP 320 (--- GAL)**

**RECOMMENDATION**

Resample at the next service interval to monitor. NOTE: Please provide information regarding reservoir capacity, filter type and micron rating with next sample.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>MW0046146</b>	MW0046168	MW0046110
Sample Date		Client Info		<b>02 Jan 2024</b>	27 Nov 2023	30 Oct 2023
Machine Age	hrs	Client Info		<b>76642</b>	503	75015
Oil Age	hrs	Client Info		<b>76642</b>	503	32202
Filter Age	hrs	Client Info		<b>0</b>	503	0
Oil Changed		Client Info		<b>Changed</b>	Changed	Changed
Filter Changed		Client Info		<b>N/A</b>	Changed	None
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

**WEAR**

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>150	<b>88</b>	75	85
Chromium	ppm	ASTM D5185m	>10	<b>0</b>	<1	<1
Nickel	ppm	ASTM D5185m	>10	<b>&lt;1</b>	0	<1
Titanium	ppm	ASTM D5185m		<b>&lt;1</b>	<1	0
Silver	ppm	ASTM D5185m		<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m	>25	<b>5</b>	3	5
Lead	ppm	ASTM D5185m	>100	<b>2</b>	1	1
Copper	ppm	ASTM D5185m	>50	<b>9</b>	10	9
Tin	ppm	ASTM D5185m	>10	<b>&lt;1</b>	<1	0
Vanadium	ppm	ASTM D5185m		<b>0</b>	0	0
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE

**CONTAMINATION**







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>50	<b>2</b>	<1	2
Potassium	ppm	ASTM D5185m	>20	<b>3</b>	0	2
Water		WC Method	>0.1	<b>NEG</b>	NEG	NEG
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	<b>NEG</b>	NEG	NEG

**FLUID CONDITION**

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		<b>4</b>	6	5
Boron	ppm	ASTM D5185m		<b>8</b>	5	5
Barium	ppm	ASTM D5185m		<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m		<b>11</b>	7	9
Manganese	ppm	ASTM D5185m		<b>1</b>	1	<1
Magnesium	ppm	ASTM D5185m		<b>3</b>	0	2
Calcium	ppm	ASTM D5185m		<b>13</b>	2	12
Phosphorus	ppm	ASTM D5185m		<b>282</b>	236	283
Zinc	ppm	ASTM D5185m		<b>22</b>	14	14
Sulfur	ppm	ASTM D5185m		<b>14003</b>	13174	14075
Acid Number (AN)	mg KOH/g	ASTM D8045		<b>1.08</b>	0.87	0.97
Visc @ 40°C	cSt	ASTM D445	320	<b>326</b>	323	325



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : MW0046146 **Received** : 31 Jan 2024  
**Lab Number** : 06075998 **Diagnosed** : 01 Feb 2024  
**Unique Number** : 10858089 **Diagnostician** : Wes Davis  
**Test Package** : MAR 2

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

**AMERICAN COMMERCIAL LINES**  
 PO BOX 610, 1701 E. MARKET STREET  
 JEFFERSONVILLE, IN  
 US 47130  
 Contact: RONALD SCHNEIDER  
 ronald.schneider@bargeacbl.com  
 T:  
 F: (812)288-1644