



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
822005-190
 Component
Diesel Engine
 Fluid
PETRO CANADA DURON SHP 15W40 (--- LTR)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		GFL0103842	GFL0097340	GFL0089523
Sample Date		Client Info		26 Jan 2024	31 Oct 2023	07 Aug 2023
Machine Age	hrs	Client Info		12466	65615	11987
Oil Age	hrs	Client Info		479	65615	1044
Filter Age	hrs	Client Info		479	0	1044
Oil Changed		Client Info		N/A	N/A	Changed
Filter Changed		Client Info		N/A	N/A	Changed
Sample Status				NORMAL	NORMAL	ABNORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>80	57	33	▲ 101
Chromium	ppm	ASTM D5185m	>5	2	1	3
Nickel	ppm	ASTM D5185m	>2	<1	<1	1
Titanium	ppm	ASTM D5185m		<1	0	<1
Silver	ppm	ASTM D5185m	>3	0	0	0
Aluminum	ppm	ASTM D5185m	>30	4	2	6
Lead	ppm	ASTM D5185m	>30	3	<1	6
Copper	ppm	ASTM D5185m	>150	2	<1	4
Tin	ppm	ASTM D5185m	>5	1	<1	2
Vanadium	ppm	ASTM D5185m		<1	0	<1
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>20	14	10	15
Potassium	ppm	ASTM D5185m	>20	7	2	11
Fuel		WC Method	>5	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	2.3	1.4	▲ 3.4
Nitration	Abs/cm	*ASTM D7624	>20	14.8	10.8	18.2
Sulfation	Abs/.1mm	*ASTM D7415	>30	26.5	21.7	32.3
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		8	5	11
Boron	ppm	ASTM D5185m	0	2	6	4
Barium	ppm	ASTM D5185m	0	0	0	0
Molybdenum	ppm	ASTM D5185m	60	48	55	67
Manganese	ppm	ASTM D5185m	0	<1	<1	1
Magnesium	ppm	ASTM D5185m	1010	988	898	1024
Calcium	ppm	ASTM D5185m	1070	1011	996	1160
Phosphorus	ppm	ASTM D5185m	1150	945	1005	1099
Zinc	ppm	ASTM D5185m	1270	1167	1211	1375
Sulfur	ppm	ASTM D5185m	2060	2563	2840	3446
Oxidation	Abs/.1mm	*ASTM D7414	>25	23.8	18.0	29.6
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	8.5	9.8	6.4
Visc @ 100°C	cSt	ASTM D445	15.4	14.3	14.2	15.4



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0103842 **Received** : 31 Jan 2024
Lab Number : 06076351 **Diagnosed** : 01 Feb 2024
Unique Number : 10858442 **Diagnostician** : Wes Davis
Test Package : FLEET

GFL Environmental - 654S - Midlothian
 12230 Deergrove Road
 Midlothian, VA
 US 23112
 Contact: Corbin Umphlet
 cumphlet@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: