



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	ATTENTION

Machine Id
INTERNATIONAL 2012

Component
Diesel Engine

Fluid
SHELL ROTELLA T 15W40 (48 QTS)

RECOMMENDATION

Oil and filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		WC0886851	WC0802042	WC0658632
Sample Date		Client Info		29 Jan 2024	14 Jul 2023	13 Jan 2023
Machine Age	mls	Client Info		410679	0	0
Oil Age	mls	Client Info		18410	0	0
Filter Age	mls	Client Info		18410	0	0
Oil Changed		Client Info		Changed	N/A	N/A
Filter Changed		Client Info		Changed	N/A	N/A
Sample Status				ATTENTION	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>165	24	19	19
Chromium	ppm	ASTM D5185m	>5	2	<1	<1
Nickel	ppm	ASTM D5185m	>4	0	0	0
Titanium	ppm	ASTM D5185m	>2	<1	<1	<1
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>20	3	<1	2
Lead	ppm	ASTM D5185m	>150	5	2	4
Copper	ppm	ASTM D5185m	>90	2	<1	<1
Tin	ppm	ASTM D5185m	>5	1	<1	<1
Vanadium	ppm	ASTM D5185m		<1	<1	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION

Fuel content negligible. There is no indication of any contamination in the oil.


Silicon	ppm	ASTM D5185m	>35	7	4	5
Potassium	ppm	ASTM D5185m	>20	2	0	1
Fuel	%	ASTM D3524	>3.0	0.4	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>7.5	0.5	0.6	0.5
Nitration	Abs/cm	*ASTM D7624	>20	10.5	11.1	10.8
Sulfation	Abs/.1mm	*ASTM D7415	>30	24.0	23.6	24.9
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION


The oil viscosity is lower than normal. The BN result indicates that there is suitable alkalinity remaining in the oil. Confirm oil type.

Sodium	ppm	ASTM D5185m		2	2	2
Boron	ppm	ASTM D5185m	316	33	22	42
Barium	ppm	ASTM D5185m	0.0	0	0	0
Molybdenum	ppm	ASTM D5185m	1.2	46	67	63
Manganese	ppm	ASTM D5185m		<1	<1	<1
Magnesium	ppm	ASTM D5185m	24	664	521	390
Calcium	ppm	ASTM D5185m	2292	1275	2041	2096
Phosphorus	ppm	ASTM D5185m	1064	966	1161	1090
Zinc	ppm	ASTM D5185m	1160	1180	1383	1366
Sulfur	ppm	ASTM D5185m	4996	2704	4013	4006
Oxidation	Abs/.1mm	*ASTM D7414	>25	20.0	19.2	21.0
Base Number (BN)	mg KOH/g	ASTM D2896	10.1	6.3	6.8	6.1
Visc @ 100°C	cSt	ASTM D445	15.7	▲ 12.3	13.5	14.2


▲ Viscosity @ 100°C




Ferrous Alloys




Fuel Dilution




Non-ferrous Metals




Base Number



▲ Viscosity @ 100°C



Base Number



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : WC0886851 **Received** : 01 Feb 2024
Lab Number : 06076552 **Tested** : 05 Feb 2024
Unique Number : 10858643 **Diagnosed** : 05 Feb 2024 - Jonathan Hester
Test Package : FLEET (Additional Tests: FuelDilution, PercentFuel)

CARCO TRANSPORTATION
 2801 MIDLAND BLVD.
 FORT SMITH, AR
 US 72904
 Contact: RON BALL
 rball@carcotrans.com
 T: (479)441-3228
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)