



PacLease

OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
846-4904
 Component
Diesel Engine
 Fluid
MOBIL DELVAC 1300 SUPER15W40 (--- GAL)

RECOMMENDATION

Oil and filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		RPL0017461	RPL0016148	RPL0011224
Sample Date		Client Info		24 Jan 2024	07 Nov 2023	31 May 2023
Machine Age	mls	Client Info		135000	121904	88102
Oil Age	mls	Client Info		135000	81214	0
Filter Age	mls	Client Info		135000	81214	0
Oil Changed		Client Info		Changed	Not Changd	Not Changd
Filter Changed		Client Info		Changed	Not Changd	Not Changd
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	88	76	42
Chromium	ppm	ASTM D5185m	>20	5	4	3
Nickel	ppm	ASTM D5185m	>4	<1	<1	1
Titanium	ppm	ASTM D5185m		<1	0	0
Silver	ppm	ASTM D5185m	>3	<1	0	<1
Aluminum	ppm	ASTM D5185m	>20	17	16	17
Lead	ppm	ASTM D5185m	>40	12	11	6
Copper	ppm	ASTM D5185m	>330	8	6	4
Tin	ppm	ASTM D5185m	>15	4	3	3
Vanadium	ppm	ASTM D5185m		<1	0	<1
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	21	18	16
Potassium	ppm	ASTM D5185m	>20	47	44	41
Fuel		WC Method	>5	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	1.3	1.1	0.7
Nitration	Abs/cm	*ASTM D7624	>20	15.2	13.7	11.4
Sulfation	Abs/.1mm	*ASTM D7415	>30	31.2	29.3	26.1
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		6	4	4
Boron	ppm	ASTM D5185m	0	20	23	22
Barium	ppm	ASTM D5185m	0	<1	<1	0
Molybdenum	ppm	ASTM D5185m	0	42	48	43
Manganese	ppm	ASTM D5185m		2	2	2
Magnesium	ppm	ASTM D5185m	0	411	482	535
Calcium	ppm	ASTM D5185m		1645	1757	1776
Phosphorus	ppm	ASTM D5185m		727	844	792
Zinc	ppm	ASTM D5185m		919	1062	1022
Sulfur	ppm	ASTM D5185m		2153	2661	3013
Oxidation	Abs/.1mm	*ASTM D7414	>25	36.3	32.9	28.2
Base Number (BN)	mg KOH/g	ASTM D2896	9.4	3.9	4.4	6.0
Visc @ 100°C	cSt	ASTM D445	14	14.3	13.9	13.3



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : RPL0017461 **Received** : 01 Feb 2024
Lab Number : 06076562 **Diagnosed** : 02 Feb 2024
Unique Number : 10858653 **Diagnostician** : Don Baldrige
Test Package : FLEET

RTL PACLEASE - 7007 - Fontana
 3121 South Riverside
 Bloomington, CA
 US 92316
 Contact: Rudy Trevizo
 TrevizoR@RushEnterprises.Com
 T: (909)829-1044
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)