



WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>



Machine Id  
**413038**  
Component  
**Diesel Engine**  
Fluid  
**PETRO CANADA DURON SHP 15W40 (--- GAL)**

**RECOMMENDATION**

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>GFL0110904</b>	GFL0090931	GFL0103033
Sample Date		Client Info		<b>25 Jan 2024</b>	21 Dec 2023	28 Nov 2023
Machine Age	hrs	Client Info		<b>2992</b>	2852	2686
Oil Age	hrs	Client Info		<b>140</b>	166	0
Filter Age	hrs	Client Info		<b>0</b>	0	0
Oil Changed		Client Info		<b>Changed</b>	Changed	Changed
Filter Changed		Client Info		<b>Changed</b>	Changed	Changed
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

**WEAR**

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>120	<b>&lt;1</b>	10	4
Chromium	ppm	ASTM D5185m	>20	<b>&lt;1</b>	<1	<1
Nickel	ppm	ASTM D5185m	>5	<b>2</b>	4	1
Titanium	ppm	ASTM D5185m	>2	<b>&lt;1</b>	<1	0
Silver	ppm	ASTM D5185m	>2	<b>0</b>	<1	<1
Aluminum	ppm	ASTM D5185m	>20	<b>2</b>	3	4
Lead	ppm	ASTM D5185m	>40	<b>0</b>	0	<1
Copper	ppm	ASTM D5185m	>330	<b>4</b>	6	3
Tin	ppm	ASTM D5185m	>15	<b>&lt;1</b>	1	1
Vanadium	ppm	ASTM D5185m		<b>0</b>	0	0
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE

**CONTAMINATION**







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	<b>3</b>	7	4
Potassium	ppm	ASTM D5185m	>20	<b>5</b>	11	7
Fuel		WC Method	>3.0	<b>&lt;1.0</b>	<1.0	<1.0
Water		WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol		WC Method		<b>NEG</b>	NEG	NEG
Soot %	%	*ASTM D7844	>4	<b>0.1</b>	0.3	0.2
Nitration	Abs/cm	*ASTM D7624	>20	<b>6.1</b>	8.9	7.5
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>18.3</b>	19.7	18.9
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	<b>NEG</b>	NEG	NEG

**FLUID CONDITION**

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		<b>0</b>	0	2
Boron	ppm	ASTM D5185m	0	<b>9</b>	2	2
Barium	ppm	ASTM D5185m	0	<b>&lt;1</b>	9	0
Molybdenum	ppm	ASTM D5185m	60	<b>64</b>	66	62
Manganese	ppm	ASTM D5185m	0	<b>0</b>	<1	<1
Magnesium	ppm	ASTM D5185m	1010	<b>933</b>	983	983
Calcium	ppm	ASTM D5185m	1070	<b>1093</b>	1095	1034
Phosphorus	ppm	ASTM D5185m	1150	<b>1020</b>	1085	1119
Zinc	ppm	ASTM D5185m	1270	<b>1214</b>	1268	1351
Sulfur	ppm	ASTM D5185m	2060	<b>3264</b>	3261	3220
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>14.6</b>	16.8	15.4
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	<b>8.7</b>	6.9	8.0
Visc @ 100°C	cSt	ASTM D445	15.4	<b>14.3</b>	13.7	13.9



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0110904 **Received** : 01 Feb 2024  
**Lab Number** : 06077536 **Diagnosed** : 02 Feb 2024  
**Unique Number** : 10859627 **Diagnostician** : Wes Davis  
**Test Package** : FLEET

**GFL Environmental - 814 - Little Rock Hauling**  
 4005 Hwy 161 N.  
 Little Rock, AR  
 US 72117  
 Contact: Brad Koenig  
 bkoenig@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)