



WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>



Machine Id  
**825022-145**  
Component  
**Diesel Engine**  
Fluid  
**PETRO CANADA DURON SHP 15W40 (--- LTR)**

**RECOMMENDATION**

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>GFL0108299</b>	GFL0098243	GFL0061550
Sample Date		Client Info		<b>29 Jan 2024</b>	02 Nov 2023	31 Aug 2023
Machine Age	hrs	Client Info		<b>24768</b>	24396	21376
Oil Age	hrs	Client Info		<b>21748</b>	24396	21376
Filter Age	hrs	Client Info		<b>0</b>	0	0
Oil Changed		Client Info		<b>Not Chngd</b>	N/A	N/A
Filter Changed		Client Info		<b>Not Chngd</b>	N/A	N/A
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

**WEAR**

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>120	<b>14</b>	3	17
Chromium	ppm	ASTM D5185m	>20	<b>&lt;1</b>	0	<1
Nickel	ppm	ASTM D5185m	>5	<b>&lt;1</b>	<1	<1
Titanium	ppm	ASTM D5185m	>2	<b>&lt;1</b>	0	0
Silver	ppm	ASTM D5185m	>2	<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m	>20	<b>4</b>	1	<1
Lead	ppm	ASTM D5185m	>40	<b>0</b>	<1	0
Copper	ppm	ASTM D5185m	>330	<b>2</b>	0	<1
Tin	ppm	ASTM D5185m	>15	<b>0</b>	<1	0
Vanadium	ppm	ASTM D5185m		<b>0</b>	<1	0
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE

**CONTAMINATION**







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	<b>3</b>	3	4
Potassium	ppm	ASTM D5185m	>20	<b>3</b>	1	1
Fuel		WC Method	>3.0	<b>&lt;1.0</b>	<1.0	<1.0
Water		WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol		WC Method		<b>NEG</b>	NEG	NEG
Soot %	%	*ASTM D7844	>4	<b>0.3</b>	0.2	0.4
Nitration	Abs/cm	*ASTM D7624	>20	<b>6.4</b>	5.9	7.7
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>17.5</b>	17.5	19.0
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	<b>NEG</b>	NEG	NEG

**FLUID CONDITION**

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		<b>0</b>	0	3
Boron	ppm	ASTM D5185m	0	<b>8</b>	18	7
Barium	ppm	ASTM D5185m	0	<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m	60	<b>59</b>	59	56
Manganese	ppm	ASTM D5185m	0	<b>0</b>	<1	<1
Magnesium	ppm	ASTM D5185m	1010	<b>865</b>	904	959
Calcium	ppm	ASTM D5185m	1070	<b>1112</b>	1079	1105
Phosphorus	ppm	ASTM D5185m	1150	<b>1011</b>	1012	1030
Zinc	ppm	ASTM D5185m	1270	<b>1176</b>	1276	1280
Sulfur	ppm	ASTM D5185m	2060	<b>3281</b>	3300	3629
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>13.2</b>	13.4	14.7
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	<b>8.8</b>	8.3	8.1
Visc @ 100°C	cSt	ASTM D445	15.4	<b>13.8</b>	13.9	13.7



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0108299  
**Lab Number** : 06077577  
**Unique Number** : 10859668  
**Test Package** : FLEET

**Received** : 01 Feb 2024  
**Tested** : 02 Feb 2024  
**Diagnosed** : 02 Feb 2024 - Wes Davis

**GFL Environmental - 652 - Fredericksburg Hauling**  
 10954 Houser Drive  
 Fredericksburg, VA  
 US 22408  
 Contact: WILLIAM MILO  
 wmilo@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:  
F: