



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
MATTEI 7C4EAR
 Component
Compressor
 Fluid
ROTOROIL 8000 (3 GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

WEAR

All component wear rates are normal.








CONTAMINATION

The water content is negligible. There is no indication of any contamination in the oil.

FLUID CONDITION

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		AN25475	AN37462	AN38818
Sample Date		Client Info		29 Jan 2024	20 Jul 2023	16 Nov 2022
Machine Age	hrs	Client Info		56425	52412	48297
Oil Age	hrs	Client Info		4013	0	6539
Filter Age	hrs	Client Info		4013	0	6539
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	ABNORMAL
Iron	ppm	ASTM D5185m	>50	8	31	▲ 108
Chromium	ppm	ASTM D5185m	>10	0	0	<1
Nickel	ppm	ASTM D5185m		0	0	0
Titanium	ppm	ASTM D5185m		<1	<1	<1
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>25	6	19	▲ 42
Lead	ppm	ASTM D5185m	>25	0	<1	<1
Copper	ppm	ASTM D5185m	>50	3	6	10
Tin	ppm	ASTM D5185m	>15	0	<1	2
Vanadium	ppm	ASTM D5185m		0	<1	0
White Metal	scalar	*Visual	NONE	LIGHT	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Silicon	ppm	ASTM D5185m	>25	6	7	16
Potassium	ppm	ASTM D5185m	>20	0	4	3
Water	%	ASTM D6304	>0.1	0.045	0.069	0.036
ppm Water	ppm	ASTM D6304	>1000	455	693.8	367.3
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG
Sodium	ppm	ASTM D5185m		6	15	53
Boron	ppm	ASTM D5185m		0	0	0
Barium	ppm	ASTM D5185m		0	0	2
Molybdenum	ppm	ASTM D5185m		0	0	0
Manganese	ppm	ASTM D5185m		0	<1	<1
Magnesium	ppm	ASTM D5185m		0	4	3
Calcium	ppm	ASTM D5185m		0	0	4
Phosphorus	ppm	ASTM D5185m	884	935	914	888
Zinc	ppm	ASTM D5185m		41	51	70
Sulfur	ppm	ASTM D5185m		13	16	69
Acid Number (AN)	mg KOH/g	ASTM D8045	0.1	0.35	0.38	0.32
Visc @ 40°C	cSt	ASTM D445	87.69	70.2	67.6	66.9



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : AN25475
Lab Number : 06083073
Unique Number : 10870518
Test Package : IND 2

Received : 07 Feb 2024
Tested : 12 Feb 2024
Diagnosed : 12 Feb 2024 - Jonathan Hester

MATTEI COMPRESSORS--OEM
 9635 LIBERTY ROAD, SUITE E
 RANDALLSTOWN, MD
 US 21133

Contact: MARTY WARD
 jward@matteicomp.com

T: (410)521-7020
 F: (410)521-7024

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)