



WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>ABNORMAL</b>



Machine Id  
**4610M**  
Component  
**Diesel Engine**  
Fluid  
**PETRO CANADA DURON SHP 15W40 (36 QTS)**

**RECOMMENDATION**

Oil and filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>GFL0110093</b>	GFL0109968	GFL0110009
Sample Date		Client Info		<b>06 Feb 2024</b>	23 Jan 2024	11 Jan 2024
Machine Age	hrs	Client Info		<b>22014</b>	21908	21783
Oil Age	hrs	Client Info		<b>600</b>	600	21783
Filter Age	hrs	Client Info		<b>600</b>	600	21783
Oil Changed		Client Info		<b>Changed</b>	N/A	Changed
Filter Changed		Client Info		<b>Changed</b>	N/A	Changed
Sample Status				<b>ABNORMAL</b>	NORMAL	NORMAL

**WEAR**

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>90	<b>72</b>	8	4
Chromium	ppm	ASTM D5185m	>20	<b>2</b>	0	0
Nickel	ppm	ASTM D5185m	>2	<b>6</b>	<1	0
Titanium	ppm	ASTM D5185m	>2	<b>&lt;1</b>	0	0
Silver	ppm	ASTM D5185m	>2	<b>&lt;1</b>	0	0
Aluminum	ppm	ASTM D5185m	>20	<b>1</b>	2	2
Lead	ppm	ASTM D5185m	>40	<b>1</b>	<1	<1
Copper	ppm	ASTM D5185m	>330	<b>37</b>	0	0
Tin	ppm	ASTM D5185m	>15	<b>3</b>	<1	<1
Vanadium	ppm	ASTM D5185m		<b>0</b>	0	0
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE

**CONTAMINATION**







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	<b>9</b>	4	3
Potassium	ppm	ASTM D5185m	>20	<b>3</b>	2	2
Fuel		WC Method	>3.0	<b>&lt;1.0</b>	<1.0	<1.0
Water		WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol		WC Method		<b>NEG</b>	NEG	NEG
Soot %	%	*ASTM D7844	>6	<b>1.5</b>	0.3	0.2
Nitration	Abs/cm	*ASTM D7624	>20	<b>16.6</b>	7.0	5.7
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>27.4</b>	19.0	18.4
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	<b>NEG</b>	NEG	NEG

**FLUID CONDITION**

The BN level is low. The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185m		<b>3</b>	6	<1
Boron	ppm	ASTM D5185m	0	<b>2</b>	2	3
Barium	ppm	ASTM D5185m	0	<b>&lt;1</b>	<1	0
Molybdenum	ppm	ASTM D5185m	60	<b>64</b>	53	57
Manganese	ppm	ASTM D5185m	0	<b>2</b>	<1	<1
Magnesium	ppm	ASTM D5185m	1010	<b>920</b>	828	922
Calcium	ppm	ASTM D5185m	1070	<b>1134</b>	892	947
Phosphorus	ppm	ASTM D5185m	1150	<b>955</b>	927	1095
Zinc	ppm	ASTM D5185m	1270	<b>1212</b>	1108	1228
Sulfur	ppm	ASTM D5185m	2060	<b>2176</b>	2624	3108
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>29.8</b>	14.9	14.1
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	<b>▲ 2.4</b>	8.6	8.4
Visc @ 100°C	cSt	ASTM D445	15.4	<b>13.6</b>	13.7	13.8



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0110093 **Received** : 08 Feb 2024  
**Lab Number** : 06083389 **Tested** : 08 Feb 2024  
**Unique Number** : 10870834 **Diagnosed** : 09 Feb 2024 - Don Baldrige  
**Test Package** : FLEET

**GFL Environmental - 410 - Michigan West**  
 39000 Van Born Rd  
 Wayne, MI  
 US 48184  
 Contact: Belal Dgheish  
 bdgheish@gflenv.com  
 T: (734)714-2340  
 F:

Certificate L2367  
 To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)