



| | |
|-----------------|---------------|
| WEAR | NORMAL |
| CONTAMINATION | NORMAL |
| FLUID CONDITION | NORMAL |



Area
020
Machine Id
912051
Component
Diesel Engine
Fluid
PETRO CANADA DURON SHP 15W40 (21 QTS)

RECOMMENDATION

Resample at the next service interval to monitor.

| Test | UOM | Method | Limit/Abn | Current | History1 | History2 |
|----------------|-----|-------------|-----------|--------------------|-------------|-------------|
| Sample Number | | Client Info | | GFL0103787 | GFL0103797 | GFL0091170 |
| Sample Date | | Client Info | | 08 Feb 2024 | 30 Nov 2023 | 13 Oct 2023 |
| Machine Age | hrs | Client Info | | 6584 | 5947 | 0 |
| Oil Age | hrs | Client Info | | 637 | 700 | 700 |
| Filter Age | hrs | Client Info | | 637 | 700 | 700 |
| Oil Changed | | Client Info | | Changed | Changed | Changed |
| Filter Changed | | Client Info | | Changed | Changed | Changed |
| Sample Status | | | | NORMAL | NORMAL | NORMAL |

WEAR

All component wear rates are normal.

| | | | | | | |
|--------------|--------|-------------|------|--------------|------|------|
| Iron | ppm | ASTM D5185m | >120 | 15 | 14 | 16 |
| Chromium | ppm | ASTM D5185m | >20 | <1 | <1 | <1 |
| Nickel | ppm | ASTM D5185m | >5 | 1 | 1 | 0 |
| Titanium | ppm | ASTM D5185m | >2 | 0 | 0 | 0 |
| Silver | ppm | ASTM D5185m | >2 | 0 | 0 | 0 |
| Aluminum | ppm | ASTM D5185m | >20 | <1 | 2 | 1 |
| Lead | ppm | ASTM D5185m | >40 | 0 | 0 | 0 |
| Copper | ppm | ASTM D5185m | >330 | 3 | 2 | 2 |
| Tin | ppm | ASTM D5185m | >15 | 0 | <1 | 1 |
| Vanadium | ppm | ASTM D5185m | | 0 | 0 | 0 |
| White Metal | scalar | *Visual | NONE | NONE | NONE | NONE |
| Yellow Metal | scalar | *Visual | NONE | NONE | NONE | NONE |

CONTAMINATION







There is no indication of any contamination in the oil.

| | | | | | | |
|------------------|----------|-------------|-------|----------------|-------|-------|
| Silicon | ppm | ASTM D5185m | >25 | 4 | 4 | 4 |
| Potassium | ppm | ASTM D5185m | >20 | <1 | 2 | <1 |
| Fuel | | WC Method | >3.0 | <1.0 | <1.0 | <1.0 |
| Water | | WC Method | >0.2 | NEG | NEG | NEG |
| Glycol | | WC Method | | NEG | NEG | NEG |
| Soot % | % | *ASTM D7844 | >4 | 0.9 | 0.7 | 0.9 |
| Nitration | Abs/cm | *ASTM D7624 | >20 | 8.3 | 7.5 | 8.7 |
| Sulfation | Abs/.1mm | *ASTM D7415 | >30 | 20.1 | 20.0 | 20.9 |
| Silt | scalar | *Visual | NONE | NONE | NONE | NONE |
| Debris | scalar | *Visual | NONE | NONE | NONE | NONE |
| Sand/Dirt | scalar | *Visual | NONE | NONE | NONE | NONE |
| Appearance | scalar | *Visual | NORML | NORML | NORML | NORML |
| Odor | scalar | *Visual | NORML | NORML | NORML | NORML |
| Emulsified Water | scalar | *Visual | >0.2 | NEG | NEG | NEG |

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

| | | | | | | |
|------------------|----------|-------------|------|--------------|------|------|
| Sodium | ppm | ASTM D5185m | | 3 | 4 | 4 |
| Boron | ppm | ASTM D5185m | 0 | 3 | 4 | 5 |
| Barium | ppm | ASTM D5185m | 0 | 0 | 2 | 0 |
| Molybdenum | ppm | ASTM D5185m | 60 | 63 | 70 | 59 |
| Manganese | ppm | ASTM D5185m | 0 | <1 | 0 | <1 |
| Magnesium | ppm | ASTM D5185m | 1010 | 958 | 1069 | 905 |
| Calcium | ppm | ASTM D5185m | 1070 | 1151 | 1296 | 1079 |
| Phosphorus | ppm | ASTM D5185m | 1150 | 987 | 1087 | 861 |
| Zinc | ppm | ASTM D5185m | 1270 | 1305 | 1410 | 1202 |
| Sulfur | ppm | ASTM D5185m | 2060 | 2825 | 5066 | 2450 |
| Oxidation | Abs/.1mm | *ASTM D7414 | >25 | 15.2 | 15.0 | 16.7 |
| Base Number (BN) | mg KOH/g | ASTM D2896 | 9.8 | 7.2 | 8.0 | 7.2 |
| Visc @ 100°C | cSt | ASTM D445 | 15.4 | 13.9 | 13.8 | 14.0 |



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0103787 **Received** : 12 Feb 2024
Lab Number : 06085610 **Tested** : 12 Feb 2024
Unique Number : 10873055 **Diagnosed** : 12 Feb 2024 - Wes Davis
Test Package : FLEET

GFL Environmental - 020 - Alamance
 703 East Gilbreath St
 Graham, NC
 US 27253
 Contact: JEREMY SHORES
 jeremy.shores@gflenv.com
 T: (336)668-3712
 F: (336)229-0526

Certificate L2367
 To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)