



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Machine Id
JOHN DEERE 410E 1DW410ETEFK697799
Component
Rear Differential
Fluid
JOHN DEERE HY-GARD HYD/TRANS (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		JR0200691	JR0175518	JR0113177
Sample Date		Client Info		09 Feb 2024	05 Jul 2023	14 Dec 2021
Machine Age	hrs	Client Info		4984	4818	3544
Oil Age	hrs	Client Info		2184	0	3046
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Not Changed	N/A	Not Changed
Filter Changed		Client Info		Changed	N/A	Not Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

PQ		ASTM D8184		16	14	19
Iron	ppm	ASTM D5185m	>500	13	27	20
Chromium	ppm	ASTM D5185m	>10	0	<1	<1
Nickel	ppm	ASTM D5185m	>10	0	0	0
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>25	0	<1	<1
Lead	ppm	ASTM D5185m	>25	0	21	<1
Copper	ppm	ASTM D5185m	>100	<1	3	3
Tin	ppm	ASTM D5185m	>10	0	0	<1
Vanadium	ppm	ASTM D5185m		0	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>75	3	3	3
Potassium	ppm	ASTM D5185m	>20	0	2	0
Water		WC Method	>.2	NEG	NEG	NEG
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>.2	NEG	NEG	NEG

FLUID CONDITION

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185m		2	0	3
Boron	ppm	ASTM D5185m	6	0	<1	0
Barium	ppm	ASTM D5185m	0	0	3	0
Molybdenum	ppm	ASTM D5185m	0	0	1	2
Manganese	ppm	ASTM D5185m		0	<1	<1
Magnesium	ppm	ASTM D5185m	145	101	97	102
Calcium	ppm	ASTM D5185m	3570	3431	3412	3370
Phosphorus	ppm	ASTM D5185m	1290	983	1010	962
Zinc	ppm	ASTM D5185m	1640	1298	1199	1139
Sulfur	ppm	ASTM D5185m		3429	3526	2916
Visc @ 40°C	cSt	ASTM D445	57.0	51.9	51.98	53.0



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513

Sample No. : JR0200691

Lab Number : 06086248

Unique Number : 10873693

Test Package : CONST (Additional Tests: PQ)

Received : 12 Feb 2024

Tested : 13 Feb 2024

Diagnosed : 13 Feb 2024 - Wes Davis

JRE - GREENVILLE

3604 HWY 264 EAST

GREENVILLE, NC

US 27834-5800

Contact: GREENVILLE SHOP

christopher.martin@jamesriverequipment.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:

F: