



LIEBHERR

OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Machine Id
LIEBHERR L586 065499-1761
Component
Front Differential
Fluid
LIEBHERR GEAR BASIC 90 LS (60 LTR)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		LH0268337	LH0258502	LH0229263
Sample Date		Client Info		07 Feb 2024	24 Aug 2023	24 Mar 2023
Machine Age	hrs	Client Info		6246	3987	3987
Oil Age	hrs	Client Info		2259	3987	1970
Filter Age	hrs	Client Info		1032	1032	0
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		None	None	None
Sample Status				NORMAL	ATTENTION	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>1500	69	17	63
Chromium	ppm	ASTM D5185m	>10	<1	2	<1
Nickel	ppm	ASTM D5185m	>4	0	0	0
Titanium	ppm	ASTM D5185m	>5	0	<1	0
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>20	0	4	0
Lead	ppm	ASTM D5185m	>5	0	7	0
Copper	ppm	ASTM D5185m	>200	36	4	50
Tin	ppm	ASTM D5185m	>10	2	<1	2
Vanadium	ppm	ASTM D5185m		0	<1	0
White Metal	scalar	*Visual	NONE	NONE	NONE	LIGHT
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION





There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>60	3	13	3
Potassium	ppm	ASTM D5185m	>20	0	3	1
Water		WC Method	>.2	NEG	NEG	NEG
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>.2	NEG	NEG	NEG

FLUID CONDITION

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185m		1	4	0
Boron	ppm	ASTM D5185m	0	0	1	<1
Barium	ppm	ASTM D5185m	0	0	0	0
Molybdenum	ppm	ASTM D5185m	0	0	0	0
Manganese	ppm	ASTM D5185m	0	2	<1	3
Magnesium	ppm	ASTM D5185m	<1	<1	3	<1
Calcium	ppm	ASTM D5185m	<1	19	▲ 1711	12
Phosphorus	ppm	ASTM D5185m	2143	2330	▲ 626	2430
Zinc	ppm	ASTM D5185m	<1	30	▲ 755	22
Sulfur	ppm	ASTM D5185m	23468	25377	▲ 5842	25056
Visc @ 40°C	cSt	ASTM D445	170	192	▲ 42.4	195



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : LH0268337
Lab Number : 06086423
Unique Number : 10873868
Test Package : CONST
Received : 12 Feb 2024
Tested : 13 Feb 2024
Diagnosed : 13 Feb 2024 - Don Baldrige

JR VINAGRO
 2208 PLAINFIELD PIKE
 JOHNSTON, RI
 US 02919
 Contact: Service Manager

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: