



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Area
(41KM9B)
Machine Id
834015
Component
Natural Gas Engine
Fluid
PETRO CANADA DURON GEO LD 15W40 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		GFL0108105	GFL0102444	GFL0102411
Sample Date		Client Info		30 Jan 2024	04 Jan 2024	13 Dec 2023
Machine Age	hrs	Client Info		882	723	582
Oil Age	hrs	Client Info		0	0	0
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	Not Changd	N/A
Filter Changed		Client Info		N/A	Not Changd	N/A
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>50	73	59	54
Chromium	ppm	ASTM D5185m	>4	1	1	<1
Nickel	ppm	ASTM D5185m	>2	3	2	1
Titanium	ppm	ASTM D5185m		<1	<1	<1
Silver	ppm	ASTM D5185m	>3	<1	<1	0
Aluminum	ppm	ASTM D5185m	>9	8	6	5
Lead	ppm	ASTM D5185m	>30	6	3	1
Copper	ppm	ASTM D5185m	>35	24	19	18
Tin	ppm	ASTM D5185m	>4	4	3	2
Vanadium	ppm	ASTM D5185m		0	0	<1
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>+100	32	30	32
Potassium	ppm	ASTM D5185m	>20	7	6	4
Water		WC Method	>0.1	NEG	NEG	NEG
Soot %	%	*ASTM D7844		0	0	0
Nitration	Abs/cm	*ASTM D7624	>20	13.8	12.9	12.5
Sulfation	Abs/.1mm	*ASTM D7415	>30	26.3	24.9	23.5
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		2	2	4
Boron	ppm	ASTM D5185m	50	3	6	5
Barium	ppm	ASTM D5185m	5	18	3	4
Molybdenum	ppm	ASTM D5185m	50	62	53	54
Manganese	ppm	ASTM D5185m	0	13	10	10
Magnesium	ppm	ASTM D5185m	560	832	778	805
Calcium	ppm	ASTM D5185m	1510	1283	1165	1208
Phosphorus	ppm	ASTM D5185m	780	768	740	679
Zinc	ppm	ASTM D5185m	870	968	894	915
Sulfur	ppm	ASTM D5185m	2040	2566	2291	2294
Oxidation	Abs/.1mm	*ASTM D7414	>25	25.0	23.2	21.8
Base Number (BN)	mg KOH/g	ASTM D2896	10.2	2.9	3.3	3.6
Visc @ 100°C	cSt	ASTM D445	15.1	14.2	14.2	14.4



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0108105
Lab Number : 06086530
Unique Number : 10873975
Test Package : FLEET

Received : 12 Feb 2024
Tested : 13 Feb 2024
Diagnosed : 13 Feb 2024 - Don Baldrige

GFL Environmental - 836 - Kansas City Hauling
 7801 East Truman Road
 Kansas City, MO
 US 64126
 Contact: Loyce Stewart
 loyce.stewart@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: