



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
109561
Component
Diesel Engine
Fluid
SHELL ROTELLA T 10W30 (--- QTS)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		IL0032955	IL0027485	IL0020054
Sample Date		Client Info		01 Feb 2024	03 Jul 2023	07 Jul 2022
Machine Age	mls	Client Info		109044	59635	48475
Oil Age	mls	Client Info		22009	12714	1554
Filter Age	mls	Client Info		22009	12714	1554
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	58	23	14
Chromium	ppm	ASTM D5185m	>20	1	<1	<1
Nickel	ppm	ASTM D5185m	>4	0	0	0
Titanium	ppm	ASTM D5185m		<1	0	0
Silver	ppm	ASTM D5185m	>3	0	0	<1
Aluminum	ppm	ASTM D5185m	>20	9	28	16
Lead	ppm	ASTM D5185m	>40	0	0	0
Copper	ppm	ASTM D5185m	>330	3	2	1
Tin	ppm	ASTM D5185m	>15	0	0	<1
Vanadium	ppm	ASTM D5185m		<1	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	6	7	10
Potassium	ppm	ASTM D5185m	>20	24	38	19
Fuel		WC Method	>5	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.8	0.4	0.2
Nitration	Abs/cm	*ASTM D7624	>20	13.0	10.8	9.0
Sulfation	Abs/.1mm	*ASTM D7415	>30	30.1	21.2	19.2
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		2	1	3
Boron	ppm	ASTM D5185m	269	81	18	99
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m	0	13	81	85
Manganese	ppm	ASTM D5185m		<1	1	<1
Magnesium	ppm	ASTM D5185m	20	78	49	49
Calcium	ppm	ASTM D5185m	1521	2813	2124	2361
Phosphorus	ppm	ASTM D5185m	948	1120	889	1101
Zinc	ppm	ASTM D5185m	893	1525	1111	1318
Sulfur	ppm	ASTM D5185m		4169	4180	4783
Oxidation	Abs/.1mm	*ASTM D7414	>25	26.5	16.5	14.7
Base Number (BN)	mg KOH/g	ASTM D2896	8.5	4.1	5	8.7
Visc @ 100°C	cSt	ASTM D445	11.0	11.7	12.6	13.7



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513

Sample No. : IL0032955

Lab Number : 06087075

Unique Number : 10874520

Test Package : FLEET

Received : 13 Feb 2024

Tested : 14 Feb 2024

Diagnosed : 14 Feb 2024 - Don Baldrige

IDEALISE OF NORTHWEST WI

611 HANSEN ROAD

GREEN BAY, WI

US 54304

Contact: GARY KOLTZ

gkoltz@pcitrucks.com

T: (920)499-6200

F: (920)499-5332

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)