



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Area

[W49604]

Machine Id

JOHN DEERE 333G 1T0333GMPMF402468

Component

Diesel Engine

Fluid

JOHN DEERE ENGINE OIL PLUS 50 II 15W40 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		JR0200193	JR0164352	JR0124032
Sample Date		Client Info		08 Feb 2024	07 Apr 2023	09 Aug 2022
Machine Age	hrs	Client Info		1479	966	588
Oil Age	hrs	Client Info		0	0	588
Filter Age	hrs	Client Info		0	0	588
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	NORMAL	ABNORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>51	29	12	35
Chromium	ppm	ASTM D5185m	>11	<1	<1	<1
Nickel	ppm	ASTM D5185m	>5	0	0	0
Titanium	ppm	ASTM D5185m		<1	0	<1
Silver	ppm	ASTM D5185m	>3	0	0	<1
Aluminum	ppm	ASTM D5185m	>31	5	<1	6
Lead	ppm	ASTM D5185m	>26	0	<1	<1
Copper	ppm	ASTM D5185m	>26	15	2	▲ 260
Tin	ppm	ASTM D5185m	>4	0	0	1
Vanadium	ppm	ASTM D5185m		<1	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>22	16	17	46
Potassium	ppm	ASTM D5185m	>20	4	0	<1
Fuel		WC Method	>2.1	<1.0	<1.0	0.3
Water		WC Method	>0.21	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.4	0.3	0.4
Nitration	Abs/cm	*ASTM D7624	>20	10.2	9.7	12.1
Sulfation	Abs/.1mm	*ASTM D7415	>30	26.0	22.8	31.5
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.21	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m	>31	0	1	9
Boron	ppm	ASTM D5185m		177	15	140
Barium	ppm	ASTM D5185m		0	0	3
Molybdenum	ppm	ASTM D5185m		304	63	219
Manganese	ppm	ASTM D5185m		0	<1	2
Magnesium	ppm	ASTM D5185m		891	904	635
Calcium	ppm	ASTM D5185m		1591	1180	1847
Phosphorus	ppm	ASTM D5185m		911	1040	848
Zinc	ppm	ASTM D5185m		1218	1261	1073
Sulfur	ppm	ASTM D5185m		2879	3739	3002
Oxidation	Abs/.1mm	*ASTM D7414	>25	21.7	19.3	28.5
Base Number (BN)	mg KOH/g	ASTM D2896	13.6	7.5	6.9	7.7
Visc @ 100°C	cSt	ASTM D445	15.4	14.0	13.5	▲ 12.4



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : JR0200193 **Received** : 13 Feb 2024
Lab Number : 06087080 **Tested** : 14 Feb 2024
Unique Number : 10874525 **Diagnosed** : 14 Feb 2024 - Don Baldrige
Test Package : CONST (Additional Tests: TBN)

JRE - ASHLAND
 11047 LEADBETTER RD
 ASHLAND, VA
 US 23005

Contact: DAVID ZIEG
 dzieg@jamesriverequipment.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T: (804)798-6001
 F: (804)798-0292