



OIL ANALYSIS REPORT

WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>

Area  
**WMR-Provo**  
 Machine Id  
**483162 SENNEBOGEN 835M 835.0.2580**  
 Component  
**Front Right Planetary**  
 Fluid  
**KENDALL NS-MP HYPOID GEAR 80W90 (--- GAL)**

**RECOMMENDATION**

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>DJJ0019838</b>	DJJ0009838	DJJ0009877
Sample Date		Client Info		<b>13 Feb 2024</b>	04 Feb 2022	12 Oct 2021
Machine Age	hrs	Client Info		<b>0</b>	3766	3270
Oil Age	hrs	Client Info		<b>0</b>	0	0
Filter Age	hrs	Client Info		<b>0</b>	0	0
Oil Changed		Client Info		<b>N/A</b>	Changed	N/A
Filter Changed		Client Info		<b>N/A</b>	Changed	N/A
Sample Status				<b>NORMAL</b>	NORMAL	ABNORMAL

**WEAR**

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>500	<b>229</b>	209	110
Chromium	ppm	ASTM D5185m	>10	<b>&lt;1</b>	<1	<1
Nickel	ppm	ASTM D5185m	>10	<b>0</b>	0	<1
Titanium	ppm	ASTM D5185m		<b>0</b>	0	<1
Silver	ppm	ASTM D5185m		<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m	>25	<b>&lt;1</b>	1	3
Lead	ppm	ASTM D5185m	>25	<b>0</b>	0	0
Copper	ppm	ASTM D5185m	>75	<b>13</b>	14	11
Tin	ppm	ASTM D5185m	>10	<b>&lt;1</b>	0	0
Vanadium	ppm	ASTM D5185m		<b>0</b>	0	<1
White Metal	scalar	*Visual	NONE	<b>NONE</b>	MODER	LIGHT
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE

**CONTAMINATION**










There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>75	<b>5</b>	4	11
Potassium	ppm	ASTM D5185m	>20	<b>&lt;1</b>	<1	0
Water		WC Method	>0.2	<b>NEG</b>	NEG	NEG
Silt	scalar	*Visual	NONE	<b>MODER</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	▲ MODER
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	<b>NEG</b>	NEG	NEG

**FLUID CONDITION**

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185m		<b>0</b>	2	1
Boron	ppm	ASTM D5185m		<b>88</b>	153	140
Barium	ppm	ASTM D5185m		<b>1</b>	0	2
Molybdenum	ppm	ASTM D5185m		<b>0</b>	<1	0
Manganese	ppm	ASTM D5185m		<b>3</b>	3	2
Magnesium	ppm	ASTM D5185m		<b>&lt;1</b>	0	2
Calcium	ppm	ASTM D5185m		<b>5</b>	18	17
Phosphorus	ppm	ASTM D5185m		<b>892</b>	986	816
Zinc	ppm	ASTM D5185m		<b>7</b>	13	11
Sulfur	ppm	ASTM D5185m		<b>22058</b>	19396	31391
Visc @ 40°C	cSt	ASTM D445	140	<b>145</b>	144	141



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : DJJ0019838  
**Lab Number** : 06087807  
**Unique Number** : 10875252  
**Test Package** : MOBCE

**WESTERN METALS RECYCLING - PROVO**  
 1776 COLORADO AVE  
 PROVO, UT  
 US 84606  
 Contact: CASEY ADAMS  
 casey.adams@wmrecycling.com  
 T: (801)972-0304  
 F: (801)373-4258

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)