



**James River  
Equipment**

**OIL ANALYSIS REPORT**

WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>

Machine Id  
**JOHN DEERE 1025R 1LV1025RTKK183534**

Component  
**Transmission (Manual)**

Fluid  
**JOHN DEERE HY-GARD HYD/TRANS (--- GAL)**

**RECOMMENDATION**

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>JR0183674</b>	---	---
Sample Date		Client Info		<b>12 Feb 2024</b>	---	---
Machine Age	hrs	Client Info		<b>326</b>	---	---
Oil Age	hrs	Client Info		<b>326</b>	---	---
Filter Age	hrs	Client Info		<b>0</b>	---	---
Oil Changed		Client Info		<b>Not Chngd</b>	---	---
Filter Changed		Client Info		<b>Changed</b>	---	---
Sample Status				<b>NORMAL</b>	---	---

**WEAR**

All component wear rates are normal.

PQ		ASTM D8184	>95	<b>22</b>	---	---
Iron	ppm	ASTM D5185m	>200	<b>40</b>	---	---
Chromium	ppm	ASTM D5185m	>5	<b>0</b>	---	---
Nickel	ppm	ASTM D5185m	>5	<b>0</b>	---	---
Titanium	ppm	ASTM D5185m		<b>0</b>	---	---
Silver	ppm	ASTM D5185m	>7	<b>0</b>	---	---
Aluminum	ppm	ASTM D5185m	>25	<b>6</b>	---	---
Lead	ppm	ASTM D5185m	>45	<b>4</b>	---	---
Copper	ppm	ASTM D5185m	>225	<b>35</b>	---	---
Tin	ppm	ASTM D5185m	>10	<b>&lt;1</b>	---	---
Vanadium	ppm	ASTM D5185m		<b>0</b>	---	---
White Metal	scalar	*Visual	NONE	<b>NONE</b>	---	---
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	---	---

**CONTAMINATION**







There is no indication of any contamination in the fluid.

Silicon	ppm	ASTM D5185m	>125	<b>21</b>	---	---
Potassium	ppm	ASTM D5185m	>20	<b>5</b>	---	---
Water		WC Method	>0.1	<b>NEG</b>	---	---
Silt	scalar	*Visual	NONE	<b>NONE</b>	---	---
Debris	scalar	*Visual	NONE	<b>NONE</b>	---	---
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	---	---
Appearance	scalar	*Visual	NORML	<b>NORML</b>	---	---
Odor	scalar	*Visual	NORML	<b>NORML</b>	---	---
Emulsified Water	scalar	*Visual	>0.1	<b>NEG</b>	---	---

**FLUID CONDITION**

The condition of the fluid is suitable for further service.

Sodium	ppm	ASTM D5185m		<b>5</b>	---	---
Boron	ppm	ASTM D5185m	6	<b>8</b>	---	---
Barium	ppm	ASTM D5185m	0	<b>5</b>	---	---
Molybdenum	ppm	ASTM D5185m	0	<b>3</b>	---	---
Manganese	ppm	ASTM D5185m		<b>2</b>	---	---
Magnesium	ppm	ASTM D5185m	145	<b>105</b>	---	---
Calcium	ppm	ASTM D5185m	3570	<b>3299</b>	---	---
Phosphorus	ppm	ASTM D5185m	1290	<b>1051</b>	---	---
Zinc	ppm	ASTM D5185m	1640	<b>1260</b>	---	---
Sulfur	ppm	ASTM D5185m		<b>3819</b>	---	---
Visc @ 40°C	cSt	ASTM D445	57.0	<b>29.1</b>	---	---



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513

**Sample No.** : JR0183674

**Lab Number** : 06088364

**Unique Number** : 10875809

**Test Package** : CONST ( Additional Tests: PQ )

**Received** : 13 Feb 2024

**Tested** : 15 Feb 2024

**Diagnosed** : 15 Feb 2024 - Sean Felton

**JRE - HARRISONBURG**

1332 GARBERS CHURCH RD

HARRISONBURG, VA

US 22801

Contact: TERRY PUFFENBARGER

terry.puffenbarger@jamesriverequipment.com

T: (540)434-4457

F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)