



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
3579C AUTOCAR ACX
 Component
Natural Gas Engine
 Fluid
CHEVRON DELO 400 NG (48 QTS)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		GFL0103160	GFL0089288	GFL0056598
Sample Date		Client Info		12 Feb 2024	25 Aug 2023	20 Mar 2023
Machine Age	hrs	Client Info		6473	5219	4132
Oil Age	hrs	Client Info		0	0	1377
Filter Age	hrs	Client Info		0	0	1377
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		N/A	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>50	17	18	11
Chromium	ppm	ASTM D5185m	>4	<1	2	2
Nickel	ppm	ASTM D5185m	>2	0	<1	<1
Titanium	ppm	ASTM D5185m		0	<1	0
Silver	ppm	ASTM D5185m	>3	0	0	0
Aluminum	ppm	ASTM D5185m	>9	2	6	3
Lead	ppm	ASTM D5185m	>30	2	7	6
Copper	ppm	ASTM D5185m	>35	<1	<1	<1
Tin	ppm	ASTM D5185m	>4	0	<1	1
Vanadium	ppm	ASTM D5185m		0	0	<1
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>+100	10	11	5
Potassium	ppm	ASTM D5185m	>20	2	<1	1
Water		WC Method	>0.1	NEG	NEG	NEG
Soot %	%	*ASTM D7844		0	0	0.1
Nitration	Abs/cm	*ASTM D7624	>20	10.0	11.5	12.2
Sulfation	Abs/.1mm	*ASTM D7415	>30	21.6	24.3	24.8
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	LIGHT	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		4	8	7
Boron	ppm	ASTM D5185m		22	14	10
Barium	ppm	ASTM D5185m		8	0	0
Molybdenum	ppm	ASTM D5185m		55	64	56
Manganese	ppm	ASTM D5185m		0	1	<1
Magnesium	ppm	ASTM D5185m		564	658	606
Calcium	ppm	ASTM D5185m		1487	1932	1785
Phosphorus	ppm	ASTM D5185m	800	728	860	752
Zinc	ppm	ASTM D5185m	880	944	1116	1051
Sulfur	ppm	ASTM D5185m		2437	3259	3106
Oxidation	Abs/.1mm	*ASTM D7414	>25	18.0	20.8	20.0
Base Number (BN)	mg KOH/g	ASTM D2896	6.1	6.7	4.5	4.1
Visc @ 100°C	cSt	ASTM D445	15.8	14.7	15.0	14.7



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0103160
Lab Number : 06088469
Unique Number : 10875914
Test Package : FLEET

Received : 14 Feb 2024
Tested : 15 Feb 2024
Diagnosed : 15 Feb 2024 - Wes Davis

GFL Environmental - 001 - Raleigh(CNG)
 3741 Conquest Drive
 Garner, NC
 US 27529

Contact: Craig Johnson
 craig.johnson@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T: (919)662-7100
 F: (919)662-7130