



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Machine Id
JOHN DEERE 310E 1DW310EXPMF710038
Component
Rear Differential
Fluid
JOHN DEERE HY-GARD HYD/TRANS (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		JR0198155	JR0171084	JR05678136
Sample Date		Client Info		08 Feb 2024	19 Jul 2023	26 Oct 2022
Machine Age	hrs	Client Info		3778	3086	2442
Oil Age	hrs	Client Info		2967	2919	0
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Not Changed	Not Changed	Not Changed
Filter Changed		Client Info		Not Changed	N/A	N/A
Sample Status				NORMAL	ABNORMAL	NORMAL

WEAR

All component wear rates are normal.

PQ	UOM	Method	Limit/Abn	Current	History1	History2
PQ		ASTM D8184		15	99	100
Iron	ppm	ASTM D5185m	>500	2	272	131
Chromium	ppm	ASTM D5185m	>10	0	2	1
Nickel	ppm	ASTM D5185m	>10	0	5	1
Titanium	ppm	ASTM D5185m		<1	<1	<1
Silver	ppm	ASTM D5185m		0	0	<1
Aluminum	ppm	ASTM D5185m	>25	2	3	3
Lead	ppm	ASTM D5185m	>25	0	<1	<1
Copper	ppm	ASTM D5185m	>100	<1	▲ 162	85
Tin	ppm	ASTM D5185m	>10	0	▲ 6	4
Vanadium	ppm	ASTM D5185m		0	<1	0
White Metal	scalar	*Visual	NONE	NONE	MODER	LIGHT
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>75	6	14	9
Potassium	ppm	ASTM D5185m	>20	1	0	2
Water		WC Method	>.2	NEG	NEG	NEG
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>.2	NEG	NEG	NEG

FLUID CONDITION

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185m		0	5	2
Boron	ppm	ASTM D5185m	6	0	14	10
Barium	ppm	ASTM D5185m	0	12	0	0
Molybdenum	ppm	ASTM D5185m	0	<1	<1	<1
Manganese	ppm	ASTM D5185m		0	13	9
Magnesium	ppm	ASTM D5185m	145	97	97	87
Calcium	ppm	ASTM D5185m	3570	3300	3556	3374
Phosphorus	ppm	ASTM D5185m	1290	1073	1045	981
Zinc	ppm	ASTM D5185m	1640	1182	1266	1207
Sulfur	ppm	ASTM D5185m		4766	4288	4008
Visc @ 40°C	cSt	ASTM D445	57.0	58.3	53.8	55.7



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : JR0198155 **Received** : 14 Feb 2024
Lab Number : 06089077 **Tested** : 15 Feb 2024
Unique Number : 10876522 **Diagnosed** : 15 Feb 2024 - Wes Davis
Test Package : CONST (Additional Tests: PQ)

JRE - CHARLOTTE
 9550 STATESVILLE ROAD
 CHARLOTTE, NC
 US 28269

Contact: CHARLOTTE SHOP
 myoung@jamesriverequipment.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T: (704)597-0211
 F: (704)596-6198