



WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>

Machine Id  
**929098-43**  
 Component  
**Diesel Engine**  
 Fluid  
**PETRO CANADA DURON SHP 15W40 (--- LTR)**

**RECOMMENDATION**

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>GFL0103120</b>	GFL0091950	GFL0091963
Sample Date		Client Info		<b>13 Feb 2024</b>	10 Nov 2023	04 Sep 2023
Machine Age	hrs	Client Info		<b>10830</b>	10419	10146
Oil Age	hrs	Client Info		<b>300</b>	273	600
Filter Age	hrs	Client Info		<b>300</b>	273	600
Oil Changed		Client Info		<b>Not Changd</b>	Not Changd	Changed
Filter Changed		Client Info		<b>Not Changd</b>	Not Changd	Changed
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

**WEAR**

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>165	<b>6</b>	<1	10
Chromium	ppm	ASTM D5185m	>5	<b>&lt;1</b>	0	<1
Nickel	ppm	ASTM D5185m	>4	<b>0</b>	0	0
Titanium	ppm	ASTM D5185m	>2	<b>0</b>	0	0
Silver	ppm	ASTM D5185m	>2	<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m	>20	<b>1</b>	<1	1
Lead	ppm	ASTM D5185m	>150	<b>&lt;1</b>	0	2
Copper	ppm	ASTM D5185m	>90	<b>4</b>	1	19
Tin	ppm	ASTM D5185m	>5	<b>&lt;1</b>	0	<1
Vanadium	ppm	ASTM D5185m		<b>0</b>	0	<1
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE

**CONTAMINATION**







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>35	<b>4</b>	3	7
Potassium	ppm	ASTM D5185m	>20	<b>1</b>	0	0
Fuel		WC Method	>3.0	<b>&lt;1.0</b>	0.4	<1.0
Water		WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol		WC Method		<b>NEG</b>	NEG	NEG
Soot %	%	*ASTM D7844	>7.5	<b>0.2</b>	0.1	0.4
Nitration	Abs/cm	*ASTM D7624	>20	<b>7.6</b>	5.9	10.5
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>19.3</b>	17.0	21.3
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	<b>NEG</b>	NEG	NEG

**FLUID CONDITION**

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		<b>19</b>	2	6
Boron	ppm	ASTM D5185m	0	<b>5</b>	6	5
Barium	ppm	ASTM D5185m	0	<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m	60	<b>60</b>	57	67
Manganese	ppm	ASTM D5185m	0	<b>&lt;1</b>	<1	<1
Magnesium	ppm	ASTM D5185m	1010	<b>1020</b>	953	1062
Calcium	ppm	ASTM D5185m	1070	<b>1042</b>	1006	1223
Phosphorus	ppm	ASTM D5185m	1150	<b>1086</b>	1016	1094
Zinc	ppm	ASTM D5185m	1270	<b>1286</b>	1256	1344
Sulfur	ppm	ASTM D5185m	2060	<b>3149</b>	3162	3565
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>15.5</b>	13.7	17.6
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	<b>8.2</b>	10.6	7.9
Visc @ 100°C	cSt	ASTM D445	15.4	<b>13.5</b>	12.1	13.5



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0103120  
**Lab Number** : 06089388  
**Unique Number** : 10876833  
**Test Package** : FLEET

**Received** : 14 Feb 2024  
**Tested** : 15 Feb 2024  
**Diagnosed** : 15 Feb 2024 - Wes Davis

**GFL Environmental - 683 - Ruckersville Hauling**  
 261 INDUSTRIAL DR  
 Ruckersville, VA  
 US 22698  
 Contact: Jaf Finney  
 jfinney@gflenv.com  
 T: (434)990-4972  
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)