



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Machine Id
1007
Component
Diesel Engine
Fluid
SHELL ROTELLA T 15W40 (25 GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		JR0195163	JR0169416	JR0137971
Sample Date		Client Info		05 Feb 2024	08 Aug 2023	30 Mar 2023
Machine Age	hrs	Client Info		11729	11049	10530
Oil Age	hrs	Client Info		500	1000	500
Filter Age	hrs	Client Info		500	1000	500
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>51	46	37	31
Chromium	ppm	ASTM D5185m	>11	<1	<1	<1
Nickel	ppm	ASTM D5185m	>5	<1	1	2
Titanium	ppm	ASTM D5185m		0	0	<1
Silver	ppm	ASTM D5185m	>3	0	0	0
Aluminum	ppm	ASTM D5185m	>31	3	4	3
Lead	ppm	ASTM D5185m	>26	1	<1	0
Copper	ppm	ASTM D5185m	>26	7	9	1
Tin	ppm	ASTM D5185m	>4	<1	<1	0
Vanadium	ppm	ASTM D5185m		0	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>22	6	6	7
Potassium	ppm	ASTM D5185m	>20	2	2	2
Fuel		WC Method	>2.1	<1.0	<1.0	<1.0
Water		WC Method	>0.21	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	1	0.7	0.5
Nitration	Abs/cm	*ASTM D7624	>20	10.2	9.4	8.1
Sulfation	Abs/.1mm	*ASTM D7415	>30	25.1	22.9	20.4
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.21	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m	>31	3	4	3
Boron	ppm	ASTM D5185m	316	3	4	3
Barium	ppm	ASTM D5185m	0.0	0	0	0
Molybdenum	ppm	ASTM D5185m	1.2	2	3	3
Manganese	ppm	ASTM D5185m		<1	<1	<1
Magnesium	ppm	ASTM D5185m	24	40	46	47
Calcium	ppm	ASTM D5185m	2292	2078	2405	2393
Phosphorus	ppm	ASTM D5185m	1064	831	914	901
Zinc	ppm	ASTM D5185m	1160	998	1158	1122
Sulfur	ppm	ASTM D5185m	4996	3114	4479	4507
Oxidation	Abs/.1mm	*ASTM D7414	>25	15.9	14.1	12.2
Base Number (BN)	mg KOH/g	ASTM D2896	10.1	5.9	6.1	6.3
Visc @ 100°C	cSt	ASTM D445	15.7	13.9	13.7	13.4



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : JR0195163 **Received** : 14 Feb 2024
Lab Number : 06089427 **Tested** : 15 Feb 2024
Unique Number : 10876872 **Diagnosed** : 15 Feb 2024 - Wes Davis
Test Package : CONST (Additional Tests: TBN)

PATRIOT DEVELOPMENT CORP
 22721 LADBROOK DRIVE STE 120
 STERLING, VA
 US 20166
 Contact: ROBERT MOSS
 robert.moss@patriotdev.net

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: