



WEAR CHECK

OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
FREIGHTLINER 307E

Component
Diesel Engine

Fluid
DIESEL ENGINE OIL SAE 40 (29 GAL)

RECOMMENDATION

Resample at the next service interval to monitor. Please specify the brand, type, and viscosity of the oil on your next sample.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		KL0013278	KL0011653	KL0011475
Sample Date		Client Info		26 Jan 2024	12 Jul 2023	28 Mar 2023
Machine Age	hrs	Client Info		13390	1608	7677
Oil Age	hrs	Client Info		0	0	0
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Filter Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>80	14	62	45
Chromium	ppm	ASTM D5185m	>5	<1	1	<1
Nickel	ppm	ASTM D5185m	>2	<1	0	0
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m	>3	0	0	0
Aluminum	ppm	ASTM D5185m	>30	4	4	3
Lead	ppm	ASTM D5185m	>30	<1	0	0
Copper	ppm	ASTM D5185m	>150	2	11	11
Tin	ppm	ASTM D5185m	>5	<1	1	0
Vanadium	ppm	ASTM D5185m		<1	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>20	7	14	14
Potassium	ppm	ASTM D5185m	>20	2	<1	0
Fuel		WC Method	>5	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.4	0.9	0.7
Nitration	Abs/cm	*ASTM D7624	>20	8.0	13.1	11.2
Sulfation	Abs/.1mm	*ASTM D7415	>30	22.2	26.5	23.0
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m	>216	1	5	3
Boron	ppm	ASTM D5185m	250	258	80	95
Barium	ppm	ASTM D5185m	10	0	3	2
Molybdenum	ppm	ASTM D5185m	100	111	67	56
Manganese	ppm	ASTM D5185m		1	6	6
Magnesium	ppm	ASTM D5185m	450	501	622	568
Calcium	ppm	ASTM D5185m	3000	1275	1765	1629
Phosphorus	ppm	ASTM D5185m	1150	1133	819	731
Zinc	ppm	ASTM D5185m	1350	1328	1040	939
Sulfur	ppm	ASTM D5185m	4250	3879	2936	2764
Oxidation	Abs/.1mm	*ASTM D7414	>25	18.4	30.1	25.7
Base Number (BN)	mg KOH/g	ASTM D2896	8.5	8.0	5.7	6.0
Visc @ 100°C	cSt	ASTM D445	14.4	13.3	14.2	13.8



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : KL0013278
Lab Number : 06089466
Unique Number : 10876911
Test Package : FLEET

Received : 14 Feb 2024
Tested : 15 Feb 2024
Diagnosed : 15 Feb 2024 - Wes Davis

CITY OF ARTESIA
 P.O. BOX 1310
 ARTESIA, NM
 US 88211

Contact: JIMMY L. BUSTAMANTE
 JBUSTAMANTE@ARTESIANNM.GOV

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T: (575)748-8812
 F: (575)746-2390