



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Machine Id
JOHN DEERE 755K 1T0755KXCKF365867

Component
Transmission

Fluid
JOHN DEERE HYDRAU (--- QTS)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		JR0195690	JR0111967	JR0083736
Sample Date		Client Info		21 Feb 2024	31 Dec 2021	19 May 2021
Machine Age	hrs	Client Info		2843	1981	1081
Oil Age	hrs	Client Info		0	0	0
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	Not Changd	Not Changd
Filter Changed		Client Info		N/A	Not Changd	Not Changd
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

PQ		ASTM D8184	>100	9	21	21
Iron	ppm	ASTM D5185m	>61	9	20	13
Chromium	ppm	ASTM D5185m	>10	<1	0	0
Nickel	ppm	ASTM D5185m		<1	<1	<1
Titanium	ppm	ASTM D5185m		<1	0	0
Silver	ppm	ASTM D5185m		<1	0	<1
Aluminum	ppm	ASTM D5185m	>20	<1	0	<1
Lead	ppm	ASTM D5185m	>9	1	1	1
Copper	ppm	ASTM D5185m	>100	6	12	9
Tin	ppm	ASTM D5185m	>3	<1	<1	0
Vanadium	ppm	ASTM D5185m		0	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION







There is no indication of any contamination in the fluid.

Silicon	ppm	ASTM D5185m	>21	2	2	<1
Potassium	ppm	ASTM D5185m	>20	1	1	1
Water		WC Method	>0.075	NEG	NEG	NEG
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.075	NEG	NEG	NEG

FLUID CONDITION

The condition of the fluid is acceptable for the time in service.

Sodium	ppm	ASTM D5185m	>30	0	0	0
Boron	ppm	ASTM D5185m		0	<1	3
Barium	ppm	ASTM D5185m		5	<1	<1
Molybdenum	ppm	ASTM D5185m		1	<1	<1
Manganese	ppm	ASTM D5185m		<1	<1	<1
Magnesium	ppm	ASTM D5185m		5	3	7
Calcium	ppm	ASTM D5185m	87	90	172	179
Phosphorus	ppm	ASTM D5185m	727	562	605	616
Zinc	ppm	ASTM D5185m	900	725	808	827
Sulfur	ppm	ASTM D5185m	1500	1559	1550	1460
Visc @ 40°C	cSt	ASTM D445	65	56.5	54.5	55.7



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513

Sample No. : JR0195690

Lab Number : 06097915

Unique Number : 10896145

Test Package : CONST (Additional Tests: PQ)

Received : 22 Feb 2024

Tested : 23 Feb 2024

Diagnosed : 23 Feb 2024 - Wes Davis

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

GANTT'S EXCAVATING

2754 TABLER STATION RD

MARTINSBURG, WV

US 25402

Contact: RANDY HAWBAKER

machineshop@ganttsexcavating.com

T: (304)229-1162

F: (304)229-6514