



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Area
[W21049-BEASLEY]
 Machine Id
JOHN DEERE 2025R 1LV2025KALK127141
 Component
Diesel Engine
 Fluid
JOHN DEERE ENGINE OIL PLUS 50 II 15W40 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		JR0204435	JR0131730	JR0117617
Sample Date		Client Info		15 Feb 2024	09 Dec 2022	18 Jan 2022
Machine Age	hrs	Client Info		248	191	149
Oil Age	hrs	Client Info		159	0	0
Filter Age	hrs	Client Info		159	0	0
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Changed	Changed	N/A
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

Metal levels are typical for a new component breaking in.

Iron	ppm	ASTM D5185m	>51	8	9	12
Chromium	ppm	ASTM D5185m	>11	<1	0	<1
Nickel	ppm	ASTM D5185m	>5	0	0	<1
Titanium	ppm	ASTM D5185m		0	0	<1
Silver	ppm	ASTM D5185m	>3	0	0	<1
Aluminum	ppm	ASTM D5185m	>31	4	2	3
Lead	ppm	ASTM D5185m	>26	0	0	1
Copper	ppm	ASTM D5185m	>26	3	2	5
Tin	ppm	ASTM D5185m	>4	0	0	<1
Vanadium	ppm	ASTM D5185m		<1	0	<1
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>22	9	11	22
Potassium	ppm	ASTM D5185m	>20	2	2	2
Fuel		WC Method	>2.1	<1.0	<1.0	<1.0
Water		WC Method	>0.21	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.1	0.1	0.1
Nitration	Abs/cm	*ASTM D7624	>20	6.8	7.7	7.4
Sulfation	Abs/.1mm	*ASTM D7415	>30	19.1	20.7	20.9
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.21	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m	>31	2	0	3
Boron	ppm	ASTM D5185m		266	270	282
Barium	ppm	ASTM D5185m		<1	0	0
Molybdenum	ppm	ASTM D5185m		238	256	254
Manganese	ppm	ASTM D5185m		<1	<1	<1
Magnesium	ppm	ASTM D5185m		864	727	833
Calcium	ppm	ASTM D5185m		1520	1463	1531
Phosphorus	ppm	ASTM D5185m		870	864	951
Zinc	ppm	ASTM D5185m		1055	1017	1144
Sulfur	ppm	ASTM D5185m		3081	3384	3332
Oxidation	Abs/.1mm	*ASTM D7414	>25	14.4	15.9	16.0
Base Number (BN)	mg KOH/g	ASTM D2896	13.6	10.2	11.0	11.2
Visc @ 100°C	cSt	ASTM D445	15.4	13.5	13.6	13.2



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513

Sample No. : JR0204435

Lab Number : 06098912

Unique Number : 10897142

Test Package : CONST (Additional Tests: TBN)

Received : 23 Feb 2024

Tested : 26 Feb 2024

Diagnosed : 26 Feb 2024 - Wes Davis

JRE - BURKEVILLE

510 WEST COLONIAL DR

BURKEVILLE, VA

US 23922

Contact: BRANDON BOLLING

bbolling@jamesriverequipment.com

T: (434)767-5578

F: (434)767-3774

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)