



WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>



Machine Id  
**122MI**  
Component  
**Diesel Engine**  
Fluid  
**PETRO CANADA DURON SHP 15W40 (--- GAL)**

**RECOMMENDATION**

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>GFL0092813</b>	GFL0092780	GFL0092742
Sample Date		Client Info		<b>21 Feb 2024</b>	25 Oct 2023	29 Aug 2023
Machine Age	hrs	Client Info		<b>18557</b>	18557	17492
Oil Age	hrs	Client Info		<b>17492</b>	18557	17492
Filter Age	hrs	Client Info		<b>0</b>	0	0
Oil Changed		Client Info		<b>Not Changd</b>	N/A	Not Changd
Filter Changed		Client Info		<b>Not Changd</b>	N/A	Not Changd
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

**WEAR**

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>120	<b>31</b>	2	12
Chromium	ppm	ASTM D5185m	>20	<b>&lt;1</b>	<1	<1
Nickel	ppm	ASTM D5185m	>5	<b>0</b>	<1	0
Titanium	ppm	ASTM D5185m	>2	<b>&lt;1</b>	0	0
Silver	ppm	ASTM D5185m	>2	<b>0</b>	<1	0
Aluminum	ppm	ASTM D5185m	>20	<b>4</b>	1	6
Lead	ppm	ASTM D5185m	>40	<b>0</b>	<1	0
Copper	ppm	ASTM D5185m	>330	<b>2</b>	<1	<1
Tin	ppm	ASTM D5185m	>15	<b>&lt;1</b>	0	<1
Vanadium	ppm	ASTM D5185m		<b>0</b>	0	0
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE

**CONTAMINATION**







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	<b>5</b>	3	5
Potassium	ppm	ASTM D5185m	>20	<b>5</b>	1	11
Fuel		WC Method	>3.0	<b>&lt;1.0</b>	<1.0	<1.0
Water		WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol		WC Method		<b>NEG</b>	NEG	NEG
Soot %	%	*ASTM D7844	>4	<b>0.5</b>	0.4	0.3
Nitration	Abs/cm	*ASTM D7624	>20	<b>9.3</b>	10.8	8.0
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>20.2</b>	20.5	22.2
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	<b>NEG</b>	NEG	NEG

**FLUID CONDITION**

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		<b>6</b>	0	19
Boron	ppm	ASTM D5185m	0	<b>6</b>	3	37
Barium	ppm	ASTM D5185m	0	<b>&lt;1</b>	4	0
Molybdenum	ppm	ASTM D5185m	60	<b>65</b>	62	37
Manganese	ppm	ASTM D5185m	0	<b>1</b>	0	<1
Magnesium	ppm	ASTM D5185m	1010	<b>888</b>	859	493
Calcium	ppm	ASTM D5185m	1070	<b>1038</b>	1029	1505
Phosphorus	ppm	ASTM D5185m	1150	<b>943</b>	916	679
Zinc	ppm	ASTM D5185m	1270	<b>1124</b>	1149	850
Sulfur	ppm	ASTM D5185m	2060	<b>2655</b>	3050	2615
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>17.1</b>	22.1	20.9
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	<b>7.1</b>	5.6	9.1
Visc @ 100°C	cSt	ASTM D445	15.4	<b>13.1</b>	14.0	13.0



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0092813  
**Lab Number** : 06099779  
**Unique Number** : 10898009  
**Test Package** : FLEET

**Received** : 26 Feb 2024  
**Tested** : 27 Feb 2024  
**Diagnosed** : 27 Feb 2024 - Wes Davis

**GFL Environmental - 455 - Flint**  
 2051 W. Bristol Rd  
 Flint Township, MI  
 US 48507  
 Contact: MARK WOMBLE  
 mwomble@gflenv.com  
 T: (586)825-9514  
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)