



WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>



Area  
**GFL981**  
Machine Id  
**FREIGHTLINER 425130-SW4504**  
Component  
**Diesel Engine**  
Fluid  
**MOBIL DELVAC ELITE 15W40 (--- GAL)**

**RECOMMENDATION**

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>GFL011347</b>	GFL0095480	---
Sample Date		Client Info		<b>29 Jan 2024</b>	21 Dec 2023	---
Machine Age	hrs	Client Info		<b>11141</b>	10960	---
Oil Age	hrs	Client Info		<b>500</b>	500	---
Filter Age	hrs	Client Info		<b>500</b>	500	---
Oil Changed		Client Info		<b>Changed</b>	Changed	---
Filter Changed		Client Info		<b>Changed</b>	Changed	---
Sample Status				<b>NORMAL</b>	NORMAL	---

**WEAR**

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>80	<b>33</b>	32	---
Chromium	ppm	ASTM D5185m	>5	<b>2</b>	1	---
Nickel	ppm	ASTM D5185m	>2	<b>0</b>	0	---
Titanium	ppm	ASTM D5185m		<b>&lt;1</b>	0	---
Silver	ppm	ASTM D5185m	>3	<b>0</b>	0	---
Aluminum	ppm	ASTM D5185m	>30	<b>6</b>	7	---
Lead	ppm	ASTM D5185m	>30	<b>0</b>	0	---
Copper	ppm	ASTM D5185m	>150	<b>3</b>	3	---
Tin	ppm	ASTM D5185m	>5	<b>0</b>	<1	---
Vanadium	ppm	ASTM D5185m		<b>0</b>	0	---
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	---
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	---

**CONTAMINATION**







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>20	<b>12</b>	8	---
Potassium	ppm	ASTM D5185m	>20	<b>1</b>	3	---
Fuel		WC Method	>5	<b>&lt;1.0</b>	<1.0	---
Water		WC Method	>0.2	<b>NEG</b>	NEG	---
Glycol		WC Method		<b>NEG</b>	NEG	---
Soot %	%	*ASTM D7844	>3	<b>0.2</b>	0.4	---
Nitration	Abs/cm	*ASTM D7624	>20	<b>9.0</b>	10.4	---
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>17.7</b>	19.1	---
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	---
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	---
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	---
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	---
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	---
Emulsified Water	scalar	*Visual	>0.2	<b>NEG</b>	NEG	---

**FLUID CONDITION**

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		<b>2</b>	2	---
Boron	ppm	ASTM D5185m		<b>108</b>	65	---
Barium	ppm	ASTM D5185m		<b>2</b>	8	---
Molybdenum	ppm	ASTM D5185m		<b>119</b>	108	---
Manganese	ppm	ASTM D5185m		<b>&lt;1</b>	<1	---
Magnesium	ppm	ASTM D5185m		<b>625</b>	639	---
Calcium	ppm	ASTM D5185m		<b>1150</b>	1205	---
Phosphorus	ppm	ASTM D5185m		<b>678</b>	696	---
Zinc	ppm	ASTM D5185m		<b>767</b>	771	---
Sulfur	ppm	ASTM D5185m		<b>2903</b>	2953	---
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>14.7</b>	16.9	---
Base Number (BN)	mg KOH/g	ASTM D2896	10.7	<b>7.0</b>	6.2	---
Visc @ 100°C	cSt	ASTM D445	15.2	<b>13.7</b>	14.1	---



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0111347  
**Lab Number** : 06099803  
**Unique Number** : 10898033  
**Test Package** : FLEET

**Received** : 26 Feb 2024  
**Tested** : 27 Feb 2024  
**Diagnosed** : 27 Feb 2024 - Don Baldrige

**GFL Environmental - 981 - Port Arthur Hauling**  
 1000 S Business Park Dr  
 Port Arthur, TX  
 US 77640

Contact: MICHAEL KAY  
 mkay@gflenv.com  
 T: (336)660-9331

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: