



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
8313041
 Component
Diesel Engine
 Fluid
DIESEL ENGINE OIL SAE 10W30 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		IL0034870	IL06019348	IL05911752
Sample Date		Client Info		16 Feb 2024	05 Sep 2023	27 Jun 2023
Machine Age	mls	Client Info		130579	129638	106531
Oil Age	mls	Client Info		0	40000	40000
Filter Age	mls	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Filter Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	19	10	37
Chromium	ppm	ASTM D5185m	>20	2	<1	3
Nickel	ppm	ASTM D5185m	>4	1	0	1
Titanium	ppm	ASTM D5185m		<1	0	0
Silver	ppm	ASTM D5185m	>3	0	0	0
Aluminum	ppm	ASTM D5185m	>20	5	3	14
Lead	ppm	ASTM D5185m	>40	2	1	5
Copper	ppm	ASTM D5185m	>330	2	<1	5
Tin	ppm	ASTM D5185m	>15	1	<1	2
Vanadium	ppm	ASTM D5185m		<1	<1	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	12	8	14
Potassium	ppm	ASTM D5185m	>20	8	5	28
Fuel		WC Method	>5	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.2	0.2	0.4
Nitration	Abs/cm	*ASTM D7624	>20	8.1	8.4	11.7
Sulfation	Abs/.1mm	*ASTM D7415	>30	22.1	22.4	23.8
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		3	2	3
Boron	ppm	ASTM D5185m	250	23	24	16
Barium	ppm	ASTM D5185m	10	34	0	0
Molybdenum	ppm	ASTM D5185m	100	42	41	48
Manganese	ppm	ASTM D5185m		1	<1	1
Magnesium	ppm	ASTM D5185m	450	439	477	472
Calcium	ppm	ASTM D5185m	3000	1401	1654	1619
Phosphorus	ppm	ASTM D5185m	1150	656	766	697
Zinc	ppm	ASTM D5185m	1350	836	872	913
Sulfur	ppm	ASTM D5185m	4250	2371	2296	2297
Oxidation	Abs/.1mm	*ASTM D7414	>25	20.6	21.0	24.2
Base Number (BN)	mg KOH/g	ASTM D2896	8.5	8.4	8.9	6.7
Visc @ 100°C	cSt	ASTM D445	10.9	10.8	11.1	11.4



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : IL0034870
Lab Number : 06099914
Unique Number : 10898144
Test Package : FLEET

Received : 26 Feb 2024
Tested : 27 Feb 2024
Diagnosed : 27 Feb 2024 - Don Baldrige

IDEALRELEASE OF ATLANTA - FULTON
 4675 BAKERS FERRY ROAD
 ATLANTA, GA
 US 30331

Contact: DAVID JOHNS
 davidjohns@idealease.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T: (404)699-5571
 F: (404)699-7420