



# OIL ANALYSIS REPORT

WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>



Area  
**Store 5 - Cross Lanes [RO#147149]**  
Machine Id  
**JOHN DEERE 1050K 1T01050PCJF323379**  
Component  
**Left Outer Final Drive**  
Fluid  
**JOHN DEERE HY-GARD HYD/TRANS (8 GAL)**

## RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>LEC0048648</b>	LEC0035507	LECP187286
Sample Date		Client Info		<b>22 Feb 2024</b>	08 Jun 2023	29 Nov 2018
Machine Age	hrs	Client Info		<b>1208</b>	643	604
Oil Age	hrs	Client Info		<b>1208</b>	643	604
Filter Age	hrs	Client Info		<b>0</b>	0	0
Oil Changed		Client Info		<b>Changed</b>	Not Changd	Not Changd
Filter Changed		Client Info		<b>N/A</b>	N/A	N/A
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

## WEAR

All component wear rates are normal.

PQ		ASTM D8184	>1250	<b>38</b>	20	38
Iron	ppm	ASTM D5185m	>750	<b>16</b>	10	12
Chromium	ppm	ASTM D5185m	>9	<b>&lt;1</b>	0	<1
Nickel	ppm	ASTM D5185m	>10	<b>0</b>	0	<1
Titanium	ppm	ASTM D5185m		<b>0</b>	0	<1
Silver	ppm	ASTM D5185m		<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m	>40	<b>1</b>	<1	<1
Lead	ppm	ASTM D5185m	>15	<b>1</b>	0	0
Copper	ppm	ASTM D5185m	>40	<b>2</b>	2	2
Tin	ppm	ASTM D5185m	>10	<b>&lt;1</b>	<1	0
Vanadium	ppm	ASTM D5185m		<b>0</b>	0	<1
White Metal	scalar	*Visual	NONE	<b>NONE</b>	LIGHT	LIGHT
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE

## CONTAMINATION







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>75	<b>4</b>	3	3
Potassium	ppm	ASTM D5185m	>20	<b>12</b>	9	3
Water		WC Method	>0.075	<b>NEG</b>	NEG	NEG
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.075	<b>NEG</b>	NEG	NEG

## FLUID CONDITION

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185m	>51	<b>3</b>	3	3
Boron	ppm	ASTM D5185m	6	<b>0</b>	0	<1
Barium	ppm	ASTM D5185m	0	<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m	0	<b>0</b>	0	0
Manganese	ppm	ASTM D5185m		<b>&lt;1</b>	<1	<1
Magnesium	ppm	ASTM D5185m	145	<b>102</b>	101	100
Calcium	ppm	ASTM D5185m	3570	<b>3346</b>	3487	3439
Phosphorus	ppm	ASTM D5185m	1290	<b>989</b>	1022	925
Zinc	ppm	ASTM D5185m	1640	<b>1274</b>	1302	1177
Sulfur	ppm	ASTM D5185m		<b>3520</b>	4293	2811
Visc @ 40°C	cSt	ASTM D445	57.0	<b>57.1</b>	57.5	57.95



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : LEC0048648 **Received** : 26 Feb 2024  
**Lab Number** : 06100382 **Tested** : 27 Feb 2024  
**Unique Number** : 10898612 **Diagnosed** : 27 Feb 2024 - Wes Davis  
**Test Package** : CONST ( Additional Tests: PQ )

**LESLIE EQUIPMENT COMPANY**  
 105 TENNIS CENTER DR.  
 MARIETTA, OH  
 US 45750-9765  
 Contact: LEANNE KENDALL  
 KendalLeanne@lec1.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T: (740)373-5570