



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Machine Id
834048
Component
Diesel Engine
Fluid
PETRO CANADA DURON GEO LD 15W40 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		GFL0108069	GFL0108114	GFL0108115
Sample Date		Client Info		20 Feb 2024	30 Jan 2024	26 Jan 2024
Machine Age	hrs	Client Info		1388	1241	1221
Oil Age	hrs	Client Info		167	0	0
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Not Chngd	Not Chngd	Changed
Filter Changed		Client Info		Not Chngd	Not Chngd	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>80	0	6	33
Chromium	ppm	ASTM D5185m	>5	<1	<1	2
Nickel	ppm	ASTM D5185m	>2	0	<1	2
Titanium	ppm	ASTM D5185m		0	<1	<1
Silver	ppm	ASTM D5185m	>3	0	0	0
Aluminum	ppm	ASTM D5185m	>30	2	2	5
Lead	ppm	ASTM D5185m	>30	1	<1	3
Copper	ppm	ASTM D5185m	>150	<1	2	8
Tin	ppm	ASTM D5185m	>5	0	<1	2
Vanadium	ppm	ASTM D5185m		<1	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>20	5	6	15
Potassium	ppm	ASTM D5185m	>20	2	2	8
Fuel		WC Method	>5	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0	0	0
Nitration	Abs/cm	*ASTM D7624	>20	7.8	6.6	12.1
Sulfation	Abs/.1mm	*ASTM D7415	>30	19.2	19.4	24.0
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	LIGHT	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		6	0	0
Boron	ppm	ASTM D5185m	50	34	46	5
Barium	ppm	ASTM D5185m	5	0	13	0
Molybdenum	ppm	ASTM D5185m	50	49	51	58
Manganese	ppm	ASTM D5185m	0	<1	1	6
Magnesium	ppm	ASTM D5185m	560	586	554	669
Calcium	ppm	ASTM D5185m	1510	1654	1455	1458
Phosphorus	ppm	ASTM D5185m	780	809	715	685
Zinc	ppm	ASTM D5185m	870	967	928	1025
Sulfur	ppm	ASTM D5185m	2040	2352	2435	2189
Oxidation	Abs/.1mm	*ASTM D7414	>25	16.5	16.2	21.4
Base Number (BN)	mg KOH/g	ASTM D2896	10.2	7.9	8.5	3.2
Visc @ 100°C	cSt	ASTM D445	15.1	14.5	14.3	14.6



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0108069
Lab Number : 06100772
Unique Number : 10899002
Test Package : FLEET

Received : 26 Feb 2024
Tested : 27 Feb 2024
Diagnosed : 27 Feb 2024 - Wes Davis

GFL Environmental - 837 - Harrison TS
 22820 S State Route 291
 Harrisonville, MO
 US 64701
 Contact: JOHNNY PEREZ
 johnny.perez@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: