



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
04563
 Component
Diesel Engine
 Fluid
PETRO CANADA DURON SHP 10W30 (16 QTS)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		PCA0116243	PCA0112380	PCA0090107
Sample Date		Client Info		26 Feb 2024	21 Nov 2023	11 Jan 2023
Machine Age	hrs	Client Info		10676	10538	10061
Oil Age	hrs	Client Info		10061	10538	10061
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Filter Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	69	31	26
Chromium	ppm	ASTM D5185m	>20	3	<1	<1
Nickel	ppm	ASTM D5185m	>4	3	<1	<1
Titanium	ppm	ASTM D5185m		<1	0	0
Silver	ppm	ASTM D5185m	>3	<1	0	0
Aluminum	ppm	ASTM D5185m	>20	7	2	2
Lead	ppm	ASTM D5185m	>40	3	6	2
Copper	ppm	ASTM D5185m	>330	2	2	2
Tin	ppm	ASTM D5185m	>15	<1	0	<1
Vanadium	ppm	ASTM D5185m		<1	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	19	3	4
Potassium	ppm	ASTM D5185m	>20	21	0	1
Fuel		WC Method	>5	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.5	0.6	1
Nitration	Abs/cm	*ASTM D7624	>20	7.3	8.1	7.3
Sulfation	Abs/.1mm	*ASTM D7415	>30	19.2	20.4	19.6
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		8	3	1
Boron	ppm	ASTM D5185m	2	22	11	13
Barium	ppm	ASTM D5185m	0	2	0	4
Molybdenum	ppm	ASTM D5185m	50	102	64	63
Manganese	ppm	ASTM D5185m	0	2	<1	<1
Magnesium	ppm	ASTM D5185m	950	1361	989	848
Calcium	ppm	ASTM D5185m	1050	1638	1112	1031
Phosphorus	ppm	ASTM D5185m	995	1503	1047	931
Zinc	ppm	ASTM D5185m	1180	1840	1325	1160
Sulfur	ppm	ASTM D5185m	2600	5319	3112	3239
Oxidation	Abs/.1mm	*ASTM D7414	>25	14.7	16.4	14.2
Base Number (BN)	mg KOH/g	ASTM D2896		8.3	8.3	9.0
Visc @ 100°C	cSt	ASTM D445	12.00	11.5	11.7	11.6



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : PCA0116243
Lab Number : 06101374
Unique Number : 10899604
Test Package : FLEET
Received : 27 Feb 2024
Tested : 28 Feb 2024
Diagnosed : 29 Feb 2024 - Jonathan Hester

PERDUE FARMS - DILLON
 2047 HWY 9 WEST
 DILLON, SC
 US 29536
 Contact: KEVIN HOOKS
 kevin.hooks@perdue.com
 T: (843)841-8069
 F: (843)841-8070

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)