



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Area
(ML7053)
Machine Id
913049
Component
Diesel Engine
Fluid
PETRO CANADA DURON SHP 15W40 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		GFL0104087	GFL0068132	GFL0068136
Sample Date		Client Info		26 Feb 2024	25 Sep 2023	17 Jul 2023
Machine Age	hrs	Client Info		2648	1169	750
Oil Age	hrs	Client Info		600	600	600
Filter Age	hrs	Client Info		600	600	600
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>90	25	19	56
Chromium	ppm	ASTM D5185m	>20	4	4	3
Nickel	ppm	ASTM D5185m	>2	<1	<1	0
Titanium	ppm	ASTM D5185m	>2	<1	0	0
Silver	ppm	ASTM D5185m	>2	0	<1	0
Aluminum	ppm	ASTM D5185m	>20	17	54	31
Lead	ppm	ASTM D5185m	>40	<1	0	0
Copper	ppm	ASTM D5185m	>330	1	1	6
Tin	ppm	ASTM D5185m	>15	<1	<1	0
Vanadium	ppm	ASTM D5185m		<1	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	4	4	11
Potassium	ppm	ASTM D5185m	>20	34	81	78
Fuel		WC Method	>3.0	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>6	0.5	0.3	0.5
Nitration	Abs/cm	*ASTM D7624	>20	8.0	6.1	8.7
Sulfation	Abs/.1mm	*ASTM D7415	>30	18.9	17.3	20.8
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		4	2	2
Boron	ppm	ASTM D5185m	0	5	8	0
Barium	ppm	ASTM D5185m	0	1	0	3
Molybdenum	ppm	ASTM D5185m	60	57	63	66
Manganese	ppm	ASTM D5185m	0	<1	1	3
Magnesium	ppm	ASTM D5185m	1010	826	1028	1069
Calcium	ppm	ASTM D5185m	1070	946	1154	1194
Phosphorus	ppm	ASTM D5185m	1150	919	1175	1088
Zinc	ppm	ASTM D5185m	1270	1119	1456	1379
Sulfur	ppm	ASTM D5185m	2060	3110	3701	3927
Oxidation	Abs/.1mm	*ASTM D7414	>25	14.7	12.8	16.6
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	7.8	8.5	9.0
Visc @ 100°C	cSt	ASTM D445	15.4	13.1	13.4	13.0



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0104087
Lab Number : 06101472
Unique Number : 10899702
Test Package : FLEET

Received : 27 Feb 2024
Tested : 28 Feb 2024
Diagnosed : 28 Feb 2024 - Wes Davis

GFL Environmental - 028 - Weldon
 2211 US Highway 301
 Halifax, NC
 US 27839

Contact: TRAVIS PORCH
 tporch@gflenv.com

T: (252)532-3344

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: