



| | |
|-----------------|---------------|
| WEAR | NORMAL |
| CONTAMINATION | NORMAL |
| FLUID CONDITION | NORMAL |

Machine Id
JOHN DEERE 345G 1FF345GXCMF020838

Component
Swing Drive

Fluid
JOHN DEERE GL-5 80W90 (12 QTS)

RECOMMENDATION

Resample at the next service interval to monitor.

| Test | UOM | Method | Limit/Abn | Current | History1 | History2 |
|----------------|-----|-------------|-----------|--------------------|-------------|-------------|
| Sample Number | | Client Info | | JR0195809 | JR0192271 | JR0183806 |
| Sample Date | | Client Info | | 26 Feb 2024 | 29 Nov 2023 | 23 Aug 2023 |
| Machine Age | hrs | Client Info | | 2935 | 2406 | 1964 |
| Oil Age | hrs | Client Info | | 2493 | 442 | 1025 |
| Filter Age | hrs | Client Info | | 0 | 0 | 0 |
| Oil Changed | | Client Info | | Changed | Not Chngd | Changed |
| Filter Changed | | Client Info | | None | N/A | None |
| Sample Status | | | | NORMAL | NORMAL | NORMAL |

WEAR

All component wear rates are normal.

| | | | | | | |
|--------------|--------|-------------|------|--------------|------|------|
| PQ | | ASTM D8184 | | 43 | 19 | 35 |
| Iron | ppm | ASTM D5185m | >400 | 39 | 20 | 49 |
| Chromium | ppm | ASTM D5185m | >10 | <1 | 0 | <1 |
| Nickel | ppm | ASTM D5185m | >10 | 0 | 0 | 0 |
| Titanium | ppm | ASTM D5185m | | 0 | 0 | 0 |
| Silver | ppm | ASTM D5185m | | 0 | 0 | 0 |
| Aluminum | ppm | ASTM D5185m | >25 | 0 | 0 | <1 |
| Lead | ppm | ASTM D5185m | >50 | 0 | 0 | 0 |
| Copper | ppm | ASTM D5185m | >200 | 0 | <1 | 0 |
| Tin | ppm | ASTM D5185m | >10 | 0 | 0 | 0 |
| Vanadium | ppm | ASTM D5185m | | <1 | 0 | <1 |
| White Metal | scalar | *Visual | NONE | NONE | NONE | NONE |
| Yellow Metal | scalar | *Visual | NONE | NONE | NONE | NONE |

CONTAMINATION







There is no indication of any contamination in the oil.

| | | | | | | |
|------------------|--------|-------------|-------|--------------|-------|-------|
| Silicon | ppm | ASTM D5185m | >50 | 4 | 3 | 5 |
| Potassium | ppm | ASTM D5185m | >20 | 0 | <1 | 0 |
| Water | | WC Method | >0.2 | NEG | NEG | NEG |
| Silt | scalar | *Visual | NONE | NONE | NONE | NONE |
| Debris | scalar | *Visual | NONE | NONE | NONE | NONE |
| Sand/Dirt | scalar | *Visual | NONE | NONE | NONE | NONE |
| Appearance | scalar | *Visual | NORML | NORML | NORML | NORML |
| Odor | scalar | *Visual | NORML | NORML | NORML | NORML |
| Emulsified Water | scalar | *Visual | >0.2 | NEG | NEG | NEG |

FLUID CONDITION

The condition of the oil is acceptable for the time in service.

| | | | | | | |
|-------------|-----|-------------|--|--------------|-------|-------|
| Sodium | ppm | ASTM D5185m | | 0 | <1 | <1 |
| Boron | ppm | ASTM D5185m | | 31 | 39 | 111 |
| Barium | ppm | ASTM D5185m | | 0 | 0 | 0 |
| Molybdenum | ppm | ASTM D5185m | | 0 | 0 | 0 |
| Manganese | ppm | ASTM D5185m | | <1 | <1 | <1 |
| Magnesium | ppm | ASTM D5185m | | 1 | 4 | 3 |
| Calcium | ppm | ASTM D5185m | | 13 | 13 | 12 |
| Phosphorus | ppm | ASTM D5185m | | 450 | 465 | 636 |
| Zinc | ppm | ASTM D5185m | | 11 | 3 | 4 |
| Sulfur | ppm | ASTM D5185m | | 20038 | 18996 | 20730 |
| Visc @ 40°C | cSt | ASTM D445 | | 139 | 140 | 148 |



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : JR0195809 **Received** : 27 Feb 2024
Lab Number : 06102574 **Tested** : 29 Feb 2024
Unique Number : 10900804 **Diagnosed** : 29 Feb 2024 - Don Baldrige
Test Package : CONST (Additional Tests: PQ)

JRE - MANASSAS PARK
 9107 OWENS DRIVE
 MANASSAS PARK, VA
 US 20111

Contact: TECHNICIAN ACCOUNT
 catherine.anastasio@wearcheck.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
 F: (703)631-4715