



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
JOHN DEERE 350P 1FF350PAANF000150
 Component
Pump Drive
 Fluid
JOHN DEERE ENGINE OIL PLUS 50 II 15W40 (2 QTS)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		JR0208217	JR0190197	JR0176372
Sample Date		Client Info		27 Feb 2024	17 Oct 2023	19 Jun 2023
Machine Age	hrs	Client Info		2446	1967	1458
Oil Age	hrs	Client Info		479	1450	0
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Not Chngd	Changed	Not Chngd
Filter Changed		Client Info		None	None	N/A
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

PQ	UOM	Method	Limit/Abn	Current	History1	History2
PQ		ASTM D8184		15	17	18
Iron	ppm	ASTM D5185m	>500	57	53	42
Chromium	ppm	ASTM D5185m	>15	2	<1	<1
Nickel	ppm	ASTM D5185m	>10	<1	0	0
Titanium	ppm	ASTM D5185m		<1	<1	<1
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>20	4	4	<1
Lead	ppm	ASTM D5185m		<1	0	0
Copper	ppm	ASTM D5185m	>35	<1	0	0
Tin	ppm	ASTM D5185m	>4	<1	<1	0
Vanadium	ppm	ASTM D5185m		<1	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	MODER
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>75	32	27	23
Potassium	ppm	ASTM D5185m	>20	3	<1	<1
Water		WC Method	>0.2	NEG	NEG	NEG
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185m		2	2	3
Boron	ppm	ASTM D5185m		218	240	283
Barium	ppm	ASTM D5185m		2	<1	6
Molybdenum	ppm	ASTM D5185m		208	222	236
Manganese	ppm	ASTM D5185m		2	2	1
Magnesium	ppm	ASTM D5185m		646	725	868
Calcium	ppm	ASTM D5185m		1278	1390	1678
Phosphorus	ppm	ASTM D5185m		905	972	1058
Zinc	ppm	ASTM D5185m		942	1017	1159
Sulfur	ppm	ASTM D5185m		3552	3219	4398
Visc @ 40°C	cSt	ASTM D445	117	61.3	62.2	68.0



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : JR0208217 **Received** : 28 Feb 2024
Lab Number : 06103842 **Tested** : 29 Feb 2024
Unique Number : 10902072 **Diagnosed** : 01 Mar 2024 - Don Baldrige
Test Package : CONST (Additional Tests: PQ)

JRE - MANASSAS PARK
 9107 OWENS DRIVE
 MANASSAS PARK, VA
 US 20111

Contact: DON VEST
 dvest@jamesriverequipment.com
 T: (703)631-8500
 F: (703)631-4715

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)