



# OIL ANALYSIS REPORT

|                 |        |
|-----------------|--------|
| WEAR            | NORMAL |
| CONTAMINATION   | NORMAL |
| FLUID CONDITION | NORMAL |

Machine Id  
**70915**  
Component  
**Pump Drive**  
Fluid  
**MOBIL SHC 630 (--- GAL)**

## RECOMMENDATION

Resample at the next service interval to monitor.

| Test           | UOM | Method      | Limit/Abn | Current            | History1 | History2 |
|----------------|-----|-------------|-----------|--------------------|----------|----------|
| Sample Number  |     | Client Info |           | <b>DC0036047</b>   | ---      | ---      |
| Sample Date    |     | Client Info |           | <b>20 Feb 2024</b> | ---      | ---      |
| Machine Age    | hrs | Client Info |           | <b>1761</b>        | ---      | ---      |
| Oil Age        | hrs | Client Info |           | <b>0</b>           | ---      | ---      |
| Filter Age     | hrs | Client Info |           | <b>0</b>           | ---      | ---      |
| Oil Changed    |     | Client Info |           | <b>Changed</b>     | ---      | ---      |
| Filter Changed |     | Client Info |           | <b>N/A</b>         | ---      | ---      |
| Sample Status  |     |             |           | <b>NORMAL</b>      | ---      | ---      |

## WEAR

All component wear rates are normal.

|              |        |             |      |              |     |     |
|--------------|--------|-------------|------|--------------|-----|-----|
| Iron         | ppm    | ASTM D5185m | >500 | <b>3</b>     | --- | --- |
| Chromium     | ppm    | ASTM D5185m | >15  | <b>&lt;1</b> | --- | --- |
| Nickel       | ppm    | ASTM D5185m | >10  | <b>&lt;1</b> | --- | --- |
| Titanium     | ppm    | ASTM D5185m |      | <b>&lt;1</b> | --- | --- |
| Silver       | ppm    | ASTM D5185m |      | <b>0</b>     | --- | --- |
| Aluminum     | ppm    | ASTM D5185m | >20  | <b>&lt;1</b> | --- | --- |
| Lead         | ppm    | ASTM D5185m |      | <b>&lt;1</b> | --- | --- |
| Copper       | ppm    | ASTM D5185m | >35  | <b>&lt;1</b> | --- | --- |
| Tin          | ppm    | ASTM D5185m | >4   | <b>&lt;1</b> | --- | --- |
| Vanadium     | ppm    | ASTM D5185m |      | <b>&lt;1</b> | --- | --- |
| White Metal  | scalar | *Visual     | NONE | <b>NONE</b>  | --- | --- |
| Yellow Metal | scalar | *Visual     | NONE | <b>NONE</b>  | --- | --- |

## CONTAMINATION










There is no indication of any contamination in the oil.

|                  |        |             |       |              |     |     |
|------------------|--------|-------------|-------|--------------|-----|-----|
| Silicon          | ppm    | ASTM D5185m | >75   | <b>25</b>    | --- | --- |
| Potassium        | ppm    | ASTM D5185m | >20   | <b>1</b>     | --- | --- |
| Water            |        | WC Method   | >0.2  | <b>NEG</b>   | --- | --- |
| Silt             | scalar | *Visual     | NONE  | <b>NONE</b>  | --- | --- |
| Debris           | scalar | *Visual     | NONE  | <b>NONE</b>  | --- | --- |
| Sand/Dirt        | scalar | *Visual     | NONE  | <b>NONE</b>  | --- | --- |
| Appearance       | scalar | *Visual     | NORML | <b>NORML</b> | --- | --- |
| Odor             | scalar | *Visual     | NORML | <b>NORML</b> | --- | --- |
| Emulsified Water | scalar | *Visual     | >0.2  | <b>NEG</b>   | --- | --- |

## FLUID CONDITION

The condition of the oil is acceptable for the time in service.

|             |     |             |       |              |     |     |
|-------------|-----|-------------|-------|--------------|-----|-----|
| Sodium      | ppm | ASTM D5185m |       | <b>0</b>     | --- | --- |
| Boron       | ppm | ASTM D5185m |       | <b>&lt;1</b> | --- | --- |
| Barium      | ppm | ASTM D5185m |       | <b>1</b>     | --- | --- |
| Molybdenum  | ppm | ASTM D5185m |       | <b>&lt;1</b> | --- | --- |
| Manganese   | ppm | ASTM D5185m |       | <b>1</b>     | --- | --- |
| Magnesium   | ppm | ASTM D5185m |       | <b>0</b>     | --- | --- |
| Calcium     | ppm | ASTM D5185m |       | <b>3</b>     | --- | --- |
| Phosphorus  | ppm | ASTM D5185m |       | <b>451</b>   | --- | --- |
| Zinc        | ppm | ASTM D5185m |       | <b>11</b>    | --- | --- |
| Sulfur      | ppm | ASTM D5185m |       | <b>60</b>    | --- | --- |
| Visc @ 40°C | cSt | ASTM D445   | 217.7 | <b>219</b>   | --- | --- |



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : DC0036047  
**Lab Number** : 06103905  
**Unique Number** : 10902135  
**Test Package** : MOB 1  
**Received** : 28 Feb 2024  
**Tested** : 29 Feb 2024  
**Diagnosed** : 01 Mar 2024 - Don Baldrige

**FRANCIS O DAY**  
 14900 SOUTHLAWN LN  
 ROCKVILLE, MD  
 US 20850  
 Contact: JAMIE FORESTER

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:  
F: