



WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>

Machine Id  
**513020 KENWORTH T880**  
 Component  
**Diesel Engine**  
 Fluid  
**PETRO CANADA DURON SHP 15W40 (--- GAL)**

**RECOMMENDATION**

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>GFL0103995</b>	GFL0066589	GFL0066600
Sample Date		Client Info		<b>20 Feb 2024</b>	23 Dec 2023	16 Dec 2023
Machine Age	mls	Client Info		<b>0</b>	67902	0
Oil Age	mls	Client Info		<b>0</b>	0	0
Filter Age	mls	Client Info		<b>0</b>	0	0
Oil Changed		Client Info		<b>N/A</b>	N/A	N/A
Filter Changed		Client Info		<b>N/A</b>	N/A	N/A
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

**WEAR**

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	<b>7</b>	3	2
Chromium	ppm	ASTM D5185m	>20	<b>0</b>	0	<1
Nickel	ppm	ASTM D5185m	>4	<b>&lt;1</b>	0	0
Titanium	ppm	ASTM D5185m		<b>0</b>	0	0
Silver	ppm	ASTM D5185m	>3	<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m	>20	<b>1</b>	<1	1
Lead	ppm	ASTM D5185m	>40	<b>2</b>	0	0
Copper	ppm	ASTM D5185m	>330	<b>0</b>	<1	<1
Tin	ppm	ASTM D5185m	>15	<b>&lt;1</b>	0	<1
Vanadium	ppm	ASTM D5185m		<b>&lt;1</b>	0	<1
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE

**CONTAMINATION**







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	<b>7</b>	6	7
Potassium	ppm	ASTM D5185m	>20	<b>2</b>	3	4
Fuel		WC Method	>5	<b>&lt;1.0</b>	<1.0	<1.0
Water		WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol		WC Method		<b>NEG</b>	NEG	NEG
Soot %	%	*ASTM D7844	>3	<b>0.1</b>	0.1	0.1
Nitration	Abs/cm	*ASTM D7624	>20	<b>8.4</b>	7.5	7.0
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>17.9</b>	17.7	16.6
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	<b>NEG</b>	NEG	NEG

**FLUID CONDITION**

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		<b>&lt;1</b>	0	<1
Boron	ppm	ASTM D5185m	0	<b>8</b>	9	12
Barium	ppm	ASTM D5185m	0	<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m	60	<b>31</b>	32	32
Manganese	ppm	ASTM D5185m	0	<b>&lt;1</b>	0	<1
Magnesium	ppm	ASTM D5185m	1010	<b>70</b>	180	177
Calcium	ppm	ASTM D5185m	1070	<b>3286</b>	2468	2345
Phosphorus	ppm	ASTM D5185m	1150	<b>1129</b>	991	1006
Zinc	ppm	ASTM D5185m	1270	<b>1534</b>	1212	1173
Sulfur	ppm	ASTM D5185m	2060	<b>3864</b>	3181	3185
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>10.6</b>	11.3	10.9
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	<b>7.0</b>	7.2	7.2
Visc @ 100°C	cSt	ASTM D445	15.4	<b>16.0</b>	15.5	15.4



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0103995  
**Lab Number** : 06104158  
**Unique Number** : 10902388  
**Test Package** : FLEET

**Received** : 29 Feb 2024  
**Tested** : 29 Feb 2024  
**Diagnosed** : 02 Mar 2024 - Don Baldrige

**GFL Environmental - 980 - Northside Hauling**  
 1820 Candle Ridge Park Dr  
 Houston, TX  
 US 77073  
 Contact: Edwin Collins  
 ecolins@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:  
F: